



	25C68		
	SIZE	QTY	TOTAL Q.
	M16*45	680	8160
	M16*50	197	2364
	M16*60	272	3264
	M16*180	94	1128






MARK	SIZE	LENGTH	WIDTH	QTY	TOTAL QTY	UNIT W.	TOTAL W.
2SBG9-1	L80*80*8	5950		1	2	57.5	115.0
2SBG9-2	L80*80*8	5450		1	2	53.6	107.3
2SBG9-3	L80*80*8	5300		1	2	50.2	100.5
2SBG9-4	L80*80*8	5950		1	2	57.5	115.0
2SBG9-5	L80*80*8	5500		1	2	53.1	106.3
2SBG9-6	L80*80*8	5300		1	2	50.2	100.5
2SBG9-7	L80*80*8	5950		1	2	57.5	115.0
2SBG9-8	L80*80*8	5400		1	2	52.6	105.3
2SBG9-9	L80*80*8	5300		1	2	50.2	100.5
2SBG9-10	L80*80*8	5950		1	2	57.5	115.0
2SBG9-11	L80*80*8	5400		1	2	52.6	105.3
2SBG9-12	L80*80*8	5500		1	2	53.1	106.3
2SBG9-13	L50*50*5	1288		2	4	4.9	19.4
2SBG9-14	L50*50*5	1433		8	16	5.4	86.4
2SBG9-15	L50*50*5	1433		8	16	5.4	86.4
2SBG9-16	L50*50*5	1342		8	16	5.1	80.9
2SBG9-17	L50*50*5	1342		8	16	5.1	80.9
2SBG9-18	L50*50*5	1147		6	12	4.3	51.9
2SBG9-19	L50*50*5	1147		6	12	4.3	51.9
2SBG9-20	L50*50*5	1123		30	60	5.0	299.3
2SBG9-21	L50*50*5	1123		30	60	5.0	299.3
2SBG9-22	L50*50*5	1239		10	20	4.7	79.4
2SBG9-23	L50*50*5	1239		10	20	4.7	79.4
2SBG9-24	L50*50*5	1288		2	4	4.9	19.4
2SBG9-25	L50*50*5	1288		2	4	4.9	19.4
2SBG9-26	L50*50*5	1273		2	4	4.8	19.2
2SBG9-27	L50*50*5	1273		2	4	4.8	19.2
2SBG9-28	L50*50*5	1081		2	4	4.1	16.3
2SBG9-29	L50*50*5	1081		2	4	4.1	16.3
2SBG9-30	L80*80*8	950		28	56	9.2	513.9
2SBG9-31	L50*50*5	466		12	24	1.8	43.2
2SBG9-32	L50*50*5	796		6	12	3.0	36.0
2SBG9-33	UNP140	268		9	18	3.2	56.9
2SBG9-34	PL10	268		18	36	1.6	58.4
2SBG9-35	PL10	225	180	8	16	3.2	50.9
2SBG9-36	PL8	218	139	12	24	1.9	45.7
2SBG9-37	PL8	175	60	16	32	1.1	33.9
2SBG9-38	PL8	175	60	16	32	1.1	33.9
FPL8	PL8	50	50	75	150	0.2	23.6
TOTAL WEIGHT (Kg)							3590.1
WEIGHT							1795.0

SIZE	QTY	TOTAL Q
M16*45	546	6552

- NOTES
- 1- ALL DIMENTION ARE IN mm.
 - 2- ALL MATERIALS (MEMBERS & BRACES ...)SHALL BE HOT DIP GALVANIZED AFTER FABRICATION GALVANIZING THICKNESS FOR STRACTIONS (ACC.TO.ASTM A123)
 - 3- ALL DIMENTIONS AND DISTANCES SHALL BE CHECKED BY MANUFACTURERAND WORK-SHOP DWG. SHOULD BE BASED ON CHECKED VALUE.
 - 4- CUTTING THE FLANGES ARE NOT ACCEPTABLE.
 - 5- ALL PLATES ARE MADE OF MILD STEEL WITH ST 37 (EN 17100) : $F_y = 6400 \text{ kg/cm}^2$ AND SHOULD BE PROVIDED ACCORDING TO STABLE BOOK.
 - 6- LEG DISTANCES AT BASE OF GANTRY ARE FROM BACK TO BACK OF LEG ANGLES.
 - 7- "S" IS SHIELDWIRE ATTACHMENT POINT TO COLUMN OF GANTRY. SUSPENSION INSULATORS ATTACHMENT POINTS TO BEAM OF GANTRY
 - 8- USE BOLT M16 GRADE 8.8 $F_u = 8000 \text{ kg/cm}^2$ & $F_y = 6400 \text{ kg/cm}^2$ FOR CONNECTIONS.
 - 9- NUMBER OF BOLTS IN OTHER CONNECTIONS THAT ARE NOT SHOWN IN THIS DRAWING ARE 1*16 (HOLE #16 FOR M16).
 - 10- S-S SINGLE SHEAR D.S : DOUBLE SHEAR
 - 11- IN ADDITION TO MARKINGS REQUIRED FOR SHIPPING PURPOSES ALL CONTAINERS , BOXES , ETC. SHALL BE MARKED WITH THE FOLLOWING:
 - 12- ANGLE USED IN LEGS , BEAMS AND BRACES UP TO L140 ST37
 - 13- THE COATING OF THE BOLTS , NUTS & WASHERS OF THE CONNECTIONS SHOULD BE OF THE DACTROMET TYPE.

00	-	
REV. VERIFIED BY:	DATE:	DESCRIPTION
CLIENT:	PROJECT:	
P.G.M.I.S.E.Z	NORTHERN SITE INTERFACE 400/230 KV SUBSTATION	
Consulting:	TITLE:	
ORIDE NIBCO ENGINEERING COMPANY (P.L.C.)	STEEL STRUCTURE FOR COLUMN TYPE "2SBG9"	
DESIGNED:	NAME	PROJECT CODE:
DRAWN:	-	COMPUTER NO. :
CHECKED:	Z.KH	SCALE:
APPROVED:	-	SIZE: A1
		DRAWING NO. :

NO : 2




MARK	SIZE	LENGTH	WIDTH	QTY	TOTAL QTY	UNIT W.	TOTAL W.
2580B-1	L80*80*8	5950		1	2	51.7	103.4
2580B-2	L80*80*8	5950		1	2	51.5	103.0
2580B-3	L80*80*8	5900		1	2	51.2	102.4
2580B-4	L80*80*8	5950		1	2	51.7	103.4
2580B-5	L80*80*8	5950		1	2	51.5	103.0
2580B-6	L80*80*8	5900		1	2	51.2	102.4
2580B-7	L80*80*8	5950		1	2	51.7	103.4
2580B-8	L80*80*8	5950		1	2	51.5	103.0
2580B-9	L80*80*8	5900		1	2	51.2	102.4
2580B-10	L80*80*8	5950		1	2	51.7	103.4
2580B-11	L80*80*8	5950		1	2	51.5	103.0
2580B-12	L80*80*8	5900		1	2	51.2	102.4
2580B-13	L50*50*5	1288		2	4	4.9	19.4
2580B-14	L50*50*5	1288		2	4	4.9	19.4
2580B-15	L50*50*5	1433		16	32	5.4	172.8
2580B-16	L50*50*5	1433		16	32	5.4	172.8
2580B-17	L50*50*5	1147		6	12	4.3	51.9
2580B-18	L50*50*5	1147		6	12	4.3	51.9
2580B-19	L50*50*5	1196		6	12	5.3	63.2
2580B-20	L50*50*5	1196		6	12	5.3	63.2
2580B-21	L50*50*5	1336		10	20	4.9	98.5
2580B-22	L50*50*5	1336		10	20	4.9	98.5
2580B-23	L50*50*5	1136		16	32	4.5	144.3
2580B-24	L50*50*5	1136		16	32	4.5	144.3
2580B-25	L50*50*5	899		3	6	3.8	22.6
2580B-26	L50*50*5	899		3	6	3.8	22.6
2580B-27	L50*50*5	1288		4	8	4.9	38.8
2580B-28	L50*50*5	1288		2	4	4.9	19.4
2580B-29	L50*50*5	1288		2	4	4.9	19.4
2580B-30	L50*50*5	1081		2	4	4.1	16.3
2580B-31	L50*50*5	1081		2	4	4.1	16.3
2580B-32	L80*80*8	950		48	88	9.2	807.6
2580B-33	L50*50*5	466		20	40	1.8	70.3
2580B-34	L50*50*5	796		10	20	3.0	60.0
2580B-35	PL8	218	139	20	40	1.9	76.1
2580B-36	PL8	225	180	8	16	3.2	50.9
2580B-37	PL8	375	60	16	32	1.8	56.5
2580B-38	PL8	375	60	16	32	1.8	56.5
2580B-39	UNP160	348		9	18	3.2	56.9
TOTAL WEIGHT (kg)							3870.6
WEIGHT							1095.3

SIZE	QTY	TOTAL Q
M16*45	546	6552

- NOTES
- 1- ALL DIMENSIONS ARE IN MM.
 - 2- STEEL : ST-37
 - 3- ALL STRUCTURAL SECTIONS ARE HOT-DIP GALVANIZED ACC. TO ASTM A123
 - 4- ALL ANGLES ARE FROM MILD STEEL WITH YIELD STRENGTH 2400 Kg/cm².
 - 5- M-16 BOLTS ARE GRADE 8.8
 - 6- ALL BOLTS,NUTS,WASHERS ARE HOT-DIP GALVANIZED ACC. TO ASTM A153
 - 7-FOR EACH BOLT: ONE NUT, TWO WASHER AND ONE STANDARD SPRING WASHER ARE NEEDED.
 - 8- S IS SHIELD WIRE ATTACHMENT POINT TO COLUMN (U-BOLT M18-70)

00	-		
REV. VERIFIED BY:	DATE:	DESCRIPTION	
CLIENT:	P.G.M.I.S.E.Z	PROJECT: NORTHERN SITE INTERFACE 400/230 KV SUBSTATION	
Consulting: GUYTON WINDHOE ENGINEERING COMPANY (PVT) LTD		TITLE: STEEL STRUCTURE FOR COLUMN TYPE "4S8G8"	
DESIGNED:	NAME	PROJECT CODE:	COMPUTER NO.:
DRAWN:	-	-	-
CHECKED:	Z.R.W	SCALE:	SIZE: A1
APPROVED:	-	-	-

NO : 2



NO : 1


MARK	SIZE	LENGTH	WIDTH	QTY	TOTAL QTY	UNIT W.	TOTAL W.
2SBG7-1	L80*80*8	5950		1	1	51.7	51.7
2SBG7-2	L80*80*8	5950		1	1	51.5	51.5
2SBG7-3	L80*80*8	5900		1	1	51.2	51.2
2SBG7-4	L80*80*8	5950		1	1	51.7	51.7
2SBG7-5	L80*80*8	5950		1	1	57.5	57.5
2SBG7-6	L80*80*8	5900		1	1	51.2	51.2
2SBG7-7	L80*80*8	5950		1	1	51.7	51.7
2SBG7-8	L80*80*8	5950		1	1	57.5	57.5
2SBG7-9	L80*80*8	5900		1	1	51.2	51.2
2SBG7-10	L80*80*8	5950		1	1	51.7	51.7
2SBG7-11	L80*80*8	5950		1	1	57.5	57.5
2SBG7-12	L80*80*8	5900		1	1	51.2	51.2
2SBG7-13	L50*50*5	1288		2	2	4.9	9.7
2SBG7-14X	L50*50*5	1288		2	2	4.9	9.7
2SBG7-15	L50*50*5	1433		16	16	5.4	86.4
2SBG7-16	L50*50*5	1433		16	16	5.4	86.4
2SBG7-17	L50*50*5	1147		6	6	4.3	25.9
2SBG7-18	L50*50*5	1147		6	6	4.3	25.9
2SBG7-19	L50*50*5	1196		6	6	5.3	31.6
2SBG7-20	L50*50*5	1196		6	6	5.3	31.6
2SBG7-21	L50*50*5	1336		10	10	4.9	49.2
2SBG7-22	L50*50*5	1336		10	10	4.9	49.2
2SBG7-23	L50*50*5	1136		16	16	4.5	72.1
2SBG7-24	L50*50*5	1136		16	16	4.5	72.1
2SBG7-25	L50*50*5	899		3	3	3.8	11.3
2SBG7-26	L50*50*5	899		3	3	3.8	11.3
2SBG7-27	L50*50*5	1288		4	4	4.9	19.4
2SBG7-28	L50*50*5	1288		4	4	4.9	19.4
2SBG7-29	L50*50*5	1288		2	2	4.9	9.7
2SBG7-30	L50*50*5	1288		2	2	4.9	9.7
2SBG7-31	L50*50*5	1081		2	2	4.1	8.2
2SBG7-32	L50*50*5	1081		2	2	4.1	8.2
2SBG7-33	L80*80*8	950		44	44	9.2	403.8
2SBG7-34	L50*50*5	466		20	20	1.8	35.1
2SBG7-35	L50*50*5	796		10	10	3.0	30.0
2SBG7-36	PL8	218	139	20	20	1.9	38.1
2SBG7-37	PL8	225	180	8	8	3.2	25.4
2SBG7-38	PL6	375	60	16	16	1.8	28.8
2SBG7-39	PL6	375	60	16	16	1.8	28.8
2SBG7-40	L80*80*8	368		18	18	1.6	29.2
2SBG7-41	UNP160	368		9	9	3.2	28.4
TOTAL WEIGHT (kg)							1985.3
WEIGHT							1095.3

SIZE	QTY	TOTAL Q
2SBG1	546	6552

NOTES

- 1- ALL DIMENSIONS ARE IN MM.
- 2- STEEL - ST-37
- 3- ALL STRUCTURAL SECTIONS ARE HOT-DIP GALVANIZED ACC. TO ASTM A123
- 4- ALL ANGLES ARE FROM MILD STEEL WITH YIELD STRENGTH 2400 Kg/cm².
- 5- M-16 BOLTS ARE GRADE 8.8
- 6- ALL BOLTS,NUTS,WASHERS ARE HOT-DIP GALVANIZED ACC. TO ASTM A153
- 7-FOR EACH BOLT: ONE NUT, TWO WASHER AND ONE STANDARD SPRING WASHER ARE NEEDED.
- 8- S IS SHIELD WIRE ATTACHMENT POINT TO COLUMN (U-BOLT M18-70)

00	—	
REV.	VERIFIED BY:	DATE:
CLIENT:	P.G.M.I.S.E.Z	PROJECT: NORTHERN SITE INTERFACE 400/230 KV SUBSTATION
Consulting:	GEORGE NIKOPOLOU ENGINEERING COMPANY (S.A.S.)	TITLE: STEEL STRUCTURE FOR COLUMN TYPE "4SBG7"
DESIGNED:	NAME	PROJECT CODE:
DRAWN:	—	COMPUTER NO. :
CHECKED:	Z.KH	SCALE:
APPROVED:	—	SIZE: A1
		DRAWING NO. :




MARK	SIZE	LENGTH	WIDTH	QTY	TOTAL QTY	UNIT W.	TOTAL W.
2SCG14-1	L160*160*16	1000		2	2	38.8	77.6
2SCG14-2	L160*160*16	1000		2	2	38.8	77.6
2SCG14-3	L160*160*16	1995		2	2	77.4	154.9
2SCG14-4	L160*160*16	1995		2	2	77.4	154.9
2SCG14-5	L160*160*16	4000		2	2	155.2	310.5
2SCG14-6	L160*160*16	4000		2	2	155.2	310.5
2SCG14-7	L140*140*14	5950		2	2	174.9	349.9
2SCG14-8	L140*140*14	5950		2	2	174.9	349.9
2SCG14-9	L120*120*12	5896		2	2	127.4	254.7
2SCG14-10	L120*120*12	5896		2	2	127.4	254.7
2SCG14-11	L80*80*8	4361		2	2	42.1	84.3
2SCG14-12	L80*80*8	4361		2	2	42.1	84.3
2SCG14-15	L60*60*6	2387		4	4	12.9	51.8
2SCG14-15X	L60*60*6	2387		4	4	12.9	51.8
2SCG14-16	L60*60*6	2332		2	2	12.6	25.3
2SCG14-16X	L60*60*6	2332		2	2	12.6	25.3
2SCG14-17	L60*60*6	2262		2	2	12.3	24.5
2SCG14-17X	L60*60*6	2262		2	2	12.3	24.5
2SCG14-18	L60*60*6	2188		2	2	11.9	23.7
2SCG14-18X	L60*60*6	2188		2	2	11.9	23.7
2SCG14-19	L60*60*6	2115		2	2	11.5	22.9
2SCG14-19X	L60*60*6	2115		2	2	11.5	22.9
2SCG14-20	L60*60*6	2052		2	2	11.1	22.2
2SCG14-20X	L60*60*6	2052		2	2	11.1	22.2
2SCG14-21	L60*60*6	1949		2	2	10.6	21.1
2SCG14-21X	L60*60*6	1949		2	2	10.6	21.1
2SCG14-22	L60*60*6	1856		2	2	10.1	20.1
2SCG14-22X	L60*60*6	1856		2	2	10.1	20.1
2SCG14-23	L60*60*6	1763		2	2	9.6	19.1
2SCG14-23X	L60*60*6	1763		2	2	9.6	19.1
2SCG14-24	L80*80*8	930		4	4	9.0	35.9
2SCG14-25	L80*80*8	930		4	4	9.2	36.7
2SCG14-25X	L60*60*6	1013		4	4	3.8	15.3
2SCG14-26	L60*60*6	1643		2	2	8.9	17.8
2SCG14-27	L60*60*6	732		2	2	4.0	7.9
2SCG14-28	L60*60*6	1581		2	2	8.6	17.1
2SCG14-29	L60*60*6	471		2	2	2.6	5.1
2SCG14-30	L60*60*6	1713		2	2	9.3	18.6
2SCG14-30X	L60*60*6	1713		2	2	9.3	18.6
2SCG14-31	L60*60*6	1700		2	2	9.2	18.4
2SCG14-31X	L60*60*6	1700		2	2	9.2	18.4
2SCG14-32	L60*60*6	1740		2	2	9.4	18.9
2SCG14-32X	L60*60*6	1740		2	2	9.4	18.9
2SCG14-33	L60*60*6	1780		2	2	9.6	19.3
2SCG14-33X	L60*60*6	1780		2	2	9.6	19.3
2SCG14-34	L60*60*6	1820		2	2	9.9	19.7
2SCG14-34X	L60*60*6	1820		2	2	9.9	19.7
2SCG14-35	L60*60*6	1885		2	2	10.2	20.4
2SCG14-35X	L60*60*6	1885		2	2	10.2	20.4
2SCG14-36	L60*60*6	1910		4	4	10.4	41.4
2SCG14-36X	L60*60*6	1910		4	4	10.4	41.4
2SCG14-37	L60*60*6	1896		2	2	10.3	20.6
2SCG14-37X	L60*60*6	1896		2	2	10.3	20.6
2SCG14-38	L60*60*6	1230		2	2	6.7	13.3
2SCG14-38X	L60*60*6	1230		2	2	6.7	13.3
2SCG14-39	L80*80*8	1130		2	2	10.9	21.8
2SCG14-40	L60*60*6	1715		2	2	9.3	18.6
2SCG14-41	L60*60*6	876		2	2	4.7	9.5
2SCG14-42	L60*60*6	1622		2	2	8.8	17.6
2SCG14-43	L60*60*6	543		2	2	2.9	5.9
2SCG14-44	L60*60*6	1202		4	4	6.5	26.1
2SCG14-45	PL8	429	244	4	4	6.6	26.3
2SCG14-46	PL8	457	242	4	4	6.9	27.8
2SCG14-47	PL8	426	219	4	4	5.9	23.4
2SCG14-48	PL8	465	224	4	4	6.5	26.2
2SCG14-49	PL8	430	194	4	4	5.2	21.0
2SCG14-50	PL8	450	190	4	4	5.4	21.5
2SCG14-51	PL8	494	190	4	4	5.9	23.6
2SCG14-52	PL8	546	185	4	4	6.3	25.4
2SCG14-53	PL10	500	199	4	4	7.8	31.2
2SCG14-54	PL10	380	199	4	4	5.9	23.7
2SCG14-54X	PL10	247	165	2	2	3.6	7.2
2SCG14-55	PL8	659	224	4	4	9.7	38.7
2SCG14-56	PL8	652	224	4	4	9.2	36.7
2SCG14-57	PL8	581	205	4	4	7.5	29.9
2SCG14-58	PL8	581	205	4	4	7.5	29.9
2SCG14-59	PL8	540	185	4	4	6.3	25.1
2SCG14-60	PL8	490	185	8	8	5.7	45.5
2SCG14-61	PL8	512	189	4	4	6.1	24.3
2SCG14-62	PL10	480	470	4	4	17.7	70.8
2SCG14-63	PL10	470	380	4	4	14.0	56.1
2SCG14-64	PL10	681	185	1	1	9.9	9.9
2SCG14-65	PL8	158	138	8	8	1.4	11.0
2SCG14-66	PL15	565	150	8	8	10.0	79.8
2SCG14-67	PL15	565	140	8	8	9.3	74.5
2SCG14-68	PL15	495	130	8	8	7.6	60.6
2SCG14-69	PL12	495	120	8	8	5.6	44.8
2SCG14-70	PL12	245	95	8	8	0.4	2.9
2SCG14-71	PL12	495	120	8	8	5.6	44.8
2SCG14-72	PL12	465	100	8	8	4.4	35.0
2SCG14-73	PL12	465	90	8	8	3.9	31.5
2SCG14-73F	PL2	230	80	8	8	0.3	2.3
2SCG14-75	PL8	500	100	1	1	3.1	3.1
2SCG14-76	UNP120	50		2	2	0.7	1.3
2SCG14-77	L60*60*6	844		2	2	4.6	9.1
2SCG14-78	L60*60*6	892		2	2	4.8	9.7
2SCG14-90	PL25	420	420	4	4	34.6	138.5
2SCG14-91	PL12	460	300	4	4	13.0	52.0
2SCG14-92	PL12	370	300	4	4	10.5	41.8
2SCG14-93	PL12	300	148	12	12	4.2	50.2
2SCG14-94	PL12	300	148	8	8	4.2	33.5
2SCG14-95	PL12	300	99	4	4	2.8	11.2
2SCG14-96	PL12	300	125	8	8	3.5	28.3
FPL8	PL8	50	50	45	45	0.2	10.6
TOTAL WEIGHT (Kg)						4990.9	4990.9

NOTES

- ALL DIMENSIONS ARE IN mm.
- STEEL : ST-37
- ALL STRUCTURAL SECTIONS ARE HOT-DIP GALVANIZED ACC. TO ASTM A123
- ALL ANGLES ARE FROM MILD STEEL WITH YIELD STRENGTH 2400 Kg/cm².
- M-16 BOLTS ARE GRADE 8.8
- ALL BOLTS,NUTS,WASHERS ARE HOT-DIP GALVANIZED ACC. TO ASTM A153
- FOR EACH BOLT: ONE NUT, TWO WASHER AND ONE STANDARD SPRING WASHER ARE NEEDED.
- S IS SHIELD WIRE ATTACHMENT POINT TO COLUMN (U-BOLT M18-70)

00	—	DESCRIPTION
REV. VERIFIED BY:	DATE:	
CLIENT:	PROJECT:	
CONSULTING:	ENGINEERING COMPANY (G.K.E.C.)	
DESIGNED:	NAME	PROJECT CODE:
DRAWN:	—	COMPUTER NO. :
CHECKED:	Z.KH	SCALE:
APPROVED:	—	SIZE: A1
		DRAWING NO. :

NO : 1




MARK	SIZE	LENGTH	WIDTH	QTY	TOTAL QTY	UNIT W.	TOTAL W.
2SCG13-1	L140*140*14	1000		2	4	29.4	117.6
2SCG13-2	L140*140*14	1000		2	4	29.4	117.6
2SCG13-3	L140*140*14	3995		2	4	117.5	469.8
2SCG13-4	L140*140*14	3995		2	4	117.5	469.8
2SCG13-5	L120*120*12	5950		2	4	128.5	514.1
2SCG13-6	L120*120*12	5950		2	4	128.5	514.1
2SCG13-7	L120*120*12	2000		2	4	43.2	172.8
2SCG13-8	L120*120*12	2000		2	4	43.2	172.8
2SCG13-9	L100*100*10	5896		2	4	89.0	356.1
2SCG13-10	L100*100*10	5896		2	4	89.0	356.1
2SCG13-11	L80*80*8	4361		2	4	42.1	168.5
2SCG13-12	L80*80*8	4361		2	4	42.1	168.5
2SCG13-15	L60*60*6	2417		8	16	13.1	209.6
2SCG13-15X	L60*60*6	2417		8	16	13.1	209.6
2SCG13-16	L60*60*6	2342		2	4	12.7	50.8
2SCG13-16X	L60*60*6	2342		2	4	12.7	50.8
2SCG13-17	L60*60*6	2238		2	4	12.1	48.5
2SCG13-17X	L60*60*6	2238		2	4	12.1	48.5
2SCG13-18	L60*60*6	2150		2	4	11.7	46.6
2SCG13-18X	L60*60*6	2150		2	4	11.7	46.6
2SCG13-19	L60*60*6	2082		2	4	11.3	45.1
2SCG13-19X	L60*60*6	2082		2	4	11.3	45.1
2SCG13-20	L60*60*6	2009		2	4	10.9	43.6
2SCG13-20X	L60*60*6	2009		2	4	10.9	43.6
2SCG13-21	L60*60*6	1931		2	4	10.5	41.9
2SCG13-21X	L60*60*6	1931		2	4	10.5	41.9
2SCG13-22	L60*60*6	1863		2	4	10.1	40.4
2SCG13-22X	L60*60*6	1863		2	4	10.1	40.4
2SCG13-23	L80*80*8	930		4	8	9.0	71.9
2SCG13-24	L80*80*8	930		4	8	9.2	36.7
2SCG13-25	L50*50*5	1073		2	4	4.0	16.2
2SCG13-26X	L50*50*5	1073		2	4	4.0	16.2
2SCG13-26	L50*50*5	1631		2	4	8.8	35.4
2SCG13-27	L50*50*5	732		2	4	2.8	11.0
2SCG13-28	L60*60*6	1581		2	4	8.6	34.3
2SCG13-29	L50*50*5	471		2	4	1.8	7.1
2SCG13-30	L60*60*6	1758		2	4	9.5	38.1
2SCG13-30X	L60*60*6	1758		2	4	9.5	38.1
2SCG13-31	L60*60*6	1860		8	16	10.1	161.3
2SCG13-31X	L60*60*6	1860		8	16	10.1	161.3
2SCG13-32	L60*60*6	1885		2	4	10.2	40.9
2SCG13-32X	L60*60*6	1885		2	4	10.2	40.9
2SCG13-33	L60*60*6	1910		4	8	10.4	82.8
2SCG13-33X	L60*60*6	1910		4	8	10.4	82.8
2SCG13-34	L60*60*6	1976		2	4	10.7	42.8
2SCG13-34X	L60*60*6	1976		2	4	10.7	42.8
2SCG13-35	L80*80*8	1130		4	8	10.9	87.3
2SCG13-36	L80*80*8	1230		2	4	11.9	47.5
2SCG13-36X	L80*80*8	1230		2	4	11.9	47.5
2SCG13-36Z	L60*60*6	1715		2	4	9.3	37.2
2SCG13-37	L50*50*5	876		2	4	3.3	13.2
2SCG13-38	L60*60*6	1622		2	4	8.8	35.2
2SCG13-39	L50*50*5	543		2	4	2.0	8.2
2SCG13-40	L60*60*6	1202		2	4	6.5	26.1
2SCG13-40X	L60*60*6	1202		2	4	6.5	26.1
2SCG13-41	PL8	400	222	4	8	5.6	44.6
2SCG13-42	PL8	400	206	4	8	5.2	41.4
2SCG13-43	PL8	40	205	4	8	0.5	4.1
2SCG13-44	PL8	416	204	4	8	5.3	42.6
2SCG13-45	PL8	430	194	4	8	5.2	41.9
2SCG13-46	PL8	416	172	4	8	4.5	35.9
2SCG13-47	PL8	442	179	4	8	5.0	39.7
2SCG13-48	PL8	470	167	4	8	4.9	39.4
2SCG13-49	PL10	455	178	4	8	6.4	50.9
2SCG13-50	PL10	380	178	4	8	5.3	42.5
2SCG13-51	PL10	247	185	2	4	3.6	14.3
2SCG13-52	PL8	616	205	4	8	7.9	63.4
2SCG13-53	PL8	540	185	16	32	6.3	200.8
2SCG13-54	PL8	490	185	8	16	5.7	91.1
2SCG13-55	PL8	490	185	4	8	5.7	45.5
2SCG13-56	PL10	455	178	2	4	6.4	25.4
2SCG13-57	PL10	380	185	2	4	5.5	22.1
2SCG13-58	PL10	470	455	2	4	16.8	67.1
2SCG13-59	PL10	470	380	2	4	14.0	56.1
2SCG13-60	PL10	681	185	1	2	9.9	19.8
2SCG13-61	PL8	158	135	8	16	1.3	21.4
2SCG13-70	PL8	500	100	1	2	3.1	6.3
2SCG13-71	UNR120	50		2	4	0.7	2.7
2SCG13-72	L60*60*6	844		2	4	4.6	18.3
2SCG13-73	L60*60*6	892		2	4	4.8	19.3
2SCG13-74	PL12	495	110	8	16	5.1	82.1
2SCG13-75	PL12	495	90	8	16	4.2	67.1
2SCG13-76	PL12	465	100	8	16	4.4	70.1
2SCG13-77	PL12	465	90	8	16	3.9	63.1
2SCG13-77F	PL2	230	80	8	16	0.3	4.6
2SCG13-78	PL10	425	90	8	16	3.0	48.0
2SCG13-79	L100*100*10	425		4	8	6.4	51.3
2SCG13-79F	PL2	235	60	8	16	0.2	3.5
2SCG13-80	PL10	475	90	8	16	3.4	53.7
2SCG13-80F	PL2	235	60	8	16	0.2	3.5
2SCG13-81	L80*80*8	475		4	8	4.6	36.7
2SCG13-90	PL25	420	420	4	8	34.6	276.9
2SCG13-91	PL12	460	300	4	8	13.0	104.0
2SCG13-92	PL12	370	300	4	8	10.5	83.6
2SCG13-93	PL12	300	148	12	24	4.2	100.4
2SCG13-94	PL12	300	148	8	16	4.2	66.9
2SCG13-95	PL12	300	99	4	8	2.8	22.4
2SCG13-96	PL12	300	125	8	16	3.5	56.5
FPL8	PL8	50	50	45	90	0.2	21.2
TOTAL WEIGHT (Kg)						8212.3	
WEIGHT						4106.2	

2SCG8		
SIZE	QTY	TOTAL Q
M16*45	680	3160
M16*50	197	2364
M16*60	272	3264
M16*180	94	1128


NOTES

- ALL DIMENSIONS ARE IN mm.
- STEEL : ST-37
- ALL STRUCTURAL SECTIONS ARE HOT-DIP GALVANIZED ACC. TO ASTM A123
- ALL ANGLES ARE FROM MILD STEEL WITH YIELD STRENGTH 2400 Kg/cm².
- M-16 BOLTS ARE GRADE 8.8
- ALL BOLTS,NUTS,WASHERS ARE HOT-DIP GALVANIZED ACC. TO ASTM A153
- FOR EACH BOLT: ONE NUT, TWO WASHER AND ONE STANDARD SPRING WASHER ARE NEEDED.
- S IS SHIELD WIRE ATTACHMENT POINT TO COLUMN (U-BOLT M18-70)


00			
REV.	VERIFIED BY:	DATE:	DESCRIPTION
CLIENT:		PROJECT:	
P.G.M.I.S.E.Z		NORTHERN SITE INTERFACE 400/230 KV SUBSTATION	
Consulting:		TITLE:	
CHIROR NERDIO ENGINEERING COMPANY (O.N.E.C)		STEEL STRUCTURE FOR COLUMN TYPE "2SCG13"	
DESIGNED:	NAME	PROJECT CODE:	COMPUTER NO. :
DRAWN:			
CHECKED:	Z.KH	SCALE:	SIZE: A1
APPROVED:			DRAWING NO. :




SIDE VIEW




FRONT VIEW




SECTION A-A




SECTION B-B



DETAIL A-A



SECTION B-B



DETAIL A-A


MARK	SIZE	LENGTH	WIDTH	QTY	TOTAL QTY	UNIT W.	TOTAL W.
2SCG9-1	L120*120*12	1000		2	4	21.6	86.4
2SCG9-2	L120*120*12	1000		2	4	21.6	86.4
2SCG9-3	L120*120*12	1995		2	4	43.1	172.4
2SCG9-4	L120*120*12	1995		2	4	43.1	172.4
2SCG9-5	L120*120*12	4000		2	4	86.4	345.6
2SCG9-6	L120*120*12	4000		2	4	86.4	345.6
2SCG9-7	L120*120*12	5950		2	4	128.5	514.1
2SCG9-8	L120*120*12	5950		2	4	128.5	514.1
2SCG9-9	L100*100*10	5896		2	4	89.0	356.1
2SCG9-10	L100*100*10	5896		2	4	89.0	356.1
2SCG9-11	L80*80*8	4361		2	4	42.1	168.5
2SCG9-12	L80*80*8	4361		2	4	42.1	168.5
2SCG9-15	L60*60*6	2447		4	8	13.3	106.1
2SCG9-15X	L60*60*6	2447		4	8	13.3	106.1
2SCG9-16	L60*60*6	2342		2	4	12.7	50.8
2SCG9-16X	L60*60*6	2342		2	4	12.7	50.8
2SCG9-17	L60*60*6	2238		2	4	12.1	48.5
2SCG9-17X	L60*60*6	2238		2	4	12.1	48.5
2SCG9-18	L60*60*6	2150		2	4	11.7	46.6
2SCG9-18X	L60*60*6	2150		2	4	11.7	46.6
2SCG9-19	L60*60*6	2082		2	4	11.3	45.1
2SCG9-19X	L60*60*6	2082		2	4	11.3	45.1
2SCG9-20	L60*60*6	2009		2	4	10.9	43.6
2SCG9-20X	L60*60*6	2009		2	4	10.9	43.6
2SCG9-21	L60*60*6	1931		2	4	10.5	41.9
2SCG9-21X	L60*60*6	1931		2	4	10.5	41.9
2SCG9-22	L60*60*6	1863		2	4	10.1	40.4
2SCG9-22X	L60*60*6	1863		2	4	10.1	40.4
2SCG9-23	L80*80*8	930		4	8	9.0	71.9
2SCG9-24	L80*80*8	930		2	4	9.2	36.7
2SCG9-25	L60*60*6	1073		2	4	5.8	23.3
2SCG9-25X	L60*60*6	1073		2	4	5.8	23.3
2SCG9-26	L60*60*6	1031		2	4	5.8	23.3
2SCG9-27	L50*50*5	731		2	4	2.8	11.0
2SCG9-28	L50*50*5	1581		2	4	8.6	34.3
2SCG9-29	L50*50*5	471		2	4	1.8	7.1
2SCG9-30	L60*60*6	1816		2	4	9.8	39.4
2SCG9-30X	L60*60*6	1816		2	4	9.8	39.4
2SCG9-31	L60*60*6	1860		8	16	10.1	161.3
2SCG9-31X	L60*60*6	1860		8	16	10.1	161.3
2SCG9-32	L60*60*6	1885		2	4	10.2	40.9
2SCG9-32X	L60*60*6	1885		2	4	10.2	40.9
2SCG9-33	L60*60*6	1910		4	8	10.4	82.8
2SCG9-33X	L60*60*6	1910		4	8	10.4	82.8
2SCG9-34	L60*60*6	1976		2	4	10.7	42.8
2SCG9-34X	L60*60*6	1976		2	4	10.7	42.8
2SCG9-35	L80*80*8	1130		4	8	10.9	87.3
2SCG9-36	L60*60*6	1230		2	4	6.7	26.7
2SCG9-36X	L60*60*6	1230		2	4	6.7	26.7
2SCG9-36Z	L60*60*6	1715		2	4	9.3	37.2
2SCG9-37	L50*50*5	876		2	4	3.3	13.2
2SCG9-38	L60*60*6	1622		2	4	8.8	35.2
2SCG9-39	L50*50*5	543		2	4	2.0	8.2
2SCG9-40	L60*60*6	1202		2	4	6.5	26.1
2SCG9-40X	L60*60*6	1202		2	4	6.5	26.1
2SCG9-41	PL8	400	200	4	8	5.0	40.2
2SCG9-42	PL8	400	206	4	8	5.2	41.4
2SCG9-43	PL8	40	205	4	8	0.5	4.1
2SCG9-44	PL8	416	204	4	8	5.3	42.6
2SCG9-45	PL8	430	194	4	8	5.2	41.9
2SCG9-46	PL8	416	172	4	8	4.5	35.9
2SCG9-47	PL8	442	179	4	8	5.0	39.7
2SCG9-48	PL8	470	167	4	8	4.9	39.4
2SCG9-49	PL10	455	178	4	8	6.4	50.9
2SCG9-50	PL10	380	178	4	8	5.3	42.5
2SCG9-51	PL10	247	185	2	4	3.6	14.3
2SCG9-52	PL8	540	185	4	8	6.3	50.2
2SCG9-53	PL8	540	185	16	32	6.3	200.8
2SCG9-54	PL8	490	185	8	16	5.7	91.1
2SCG9-55	PL8	490	185	4	8	5.7	45.5
2SCG9-56	PL10	455	224	2	4	8.0	32.0
2SCG9-57	PL10	380	224	2	4	6.7	26.7
2SCG9-58	PL10	508	455	2	4	15.1	72.6
2SCG9-59	PL10	508	380	2	4	15.2	60.7
2SCG9-60	PL10	691	185	1	2	9.9	19.8
2SCG9-61	PL8	158	135	8	16	1.3	21.4
2SCG9-70	PL8	500	100	1	2	3.1	6.3
2SCG9-71	UNP120	50		2	4	0.7	2.7
2SCG9-72	L60*60*6	844		2	4	4.6	18.3
2SCG9-73	L60*60*6	892		2	4	4.8	19.3
2SCG9-74	PL10	425	110	8	16	3.7	58.7
2SCG9-75	L100*100*10	425		4	8	6.4	51.3
2SCG9-76	PL10	485	90	16	32	3.4	109.6
2SCG9-77	L100*100*10	485		8	16	7.3	117.2
2SCG9-78	PL10	475	90	8	16	3.4	53.7
2SCG9-79	L80*80*8	475		4	8	4.6	36.7
2SCG9-79F	PL2	235	60	8	16	0.2	3.5
2SCG9-90	PL25	420	420	4	8	34.6	276.9
2SCG9-91	PL12	460	300	4	8	13.0	104.0
2SCG9-92	PL12	370	300	4	8	10.5	83.6
2SCG9-93	PL12	300	148	12	24	4.2	100.4
2SCG9-94	PL12	300	148	8	16	4.2	66.9
2SCG9-95	PL12	300	99	4	8	2.8	22.4
2SCG9-96	PL12	300	125	8	16	3.5	56.5
FPL8	PL8	50	50	45	90	0.2	14.1
TOTAL WEIGHT (Kg)						7612.1	
WEIGHT						3806.1	

SIZE	QTY	TOTAL Q
M16*45	280	8160
M16*50	187	2364
M16*60	272	3264
M16*180	94	1128


- NOTES
- 1- ALL DIMENSION ARE IN mm.
 - 2- ALL MATERIALS (MEMBERS & BRACES ...) SHALL BE HOT DIP GALVANIZED AFTER FABRICATION.
 - 3- ALL DIMENSIONS AND DISTANCES SHALL BE CHECKED BY MANUFACTURER AND WORK-SHOP DWG. SHOULD BE BASED ON CHECKED VALUE.
 - 4- CUTTING THE PLANS ARE NOT ACCEPTABLE.
 - 5- ALL PLATES ARE MADE OF MILD STEEL WITH ST 37 (DIN 17100) ; $f_y = 240 \text{ kg/cm}^2$ AND SHOULD BE PROVIDED ACCORDING TO STAHL BOOK.
 - 6- LEG DISTANCES AT BASE OF GANTRY ARE FROM BACK TO BACK OF LEG ANGLES.
 - 7- "S" IS SHIELDWIRE ATTACHMENT POINT TO COLUMN OF GANTRY.
 - 8- USE BOLT M16 GRADE 8.8 $f_u = 800 \text{ kg/cm}^2$ & $f_y = 640 \text{ kg/cm}^2$ FOR CONNECTIONS.
 - 9- NUMBER OF BOLTS IN OTHER CONNECTIONS THAT ARE NOT SHOWN IN THIS DRAWING ARE 1"x16 (HOLE #16 FOR M16).
 - 10- S-S : SINGLE SHEAR D-S : DOUBLE SHEAR
 - 11- IN ADDITION TO MARKINGS REQUIRED FOR SHIPPING PURPOSES ALL CONTAINERS, BOXES, ETC. SHALL BE MARKED WITH THE FOLLOWING:
 - 12- ANGLE USED IN LEGS, BEAMS AND BRACES UP TO 1040 8757
 - 13- THE COATING OF THE BOLTS, NUTS & WASHERS OF THE CONNECTIONS SHOULD BE OF THE DACROMET TYPE.

00			
REV.	VERIFIED BY:	DATE:	DESCRIPTION
CLIENT:	PROJECT: NORTHERN SITE INTERFACE 400/230 KV SUBSTATION		
Consulting: P.G.M.I.S.E.Z	TITLE: STEEL STRUCTURE FOR COLUMN TYPE "2SCG9"		
DESIGNED:	NAME	PROJECT CODE:	COMPUTER NO. :
DRAWN:		SCALE:	SIZE: A1
CHECKED:	Z.KH		DRAWING NO. :
APPROVED:			


NO : 2




TOP VIEW



FRONT & BACK VIEW



BOTTOM VIEW




SECTION A-A

SECTION B-B


MARK	SIZE	LENGTH	WIDTH	QTY	TOTAL QTY	UNIT W.	TOTAL W.
2SBG5-1	L80*80*8	5450		1	2	52.6	105.3
2SBG5-2	L80*80*8	5350		1	2	51.7	103.4
2SBG5-3	L80*80*8	5800		1	2	56.0	112.1
2SBG5-4	L80*80*8	5450		1	2	52.6	105.3
2SBG5-5	L80*80*8	5350		1	2	51.7	103.4
2SBG5-6	L80*80*8	5800		1	2	56.0	112.1
2SBG5-7	L80*80*8	5450		1	2	52.6	105.3
2SBG5-8	L80*80*8	5350		1	2	51.7	103.4
2SBG5-9	L80*80*8	5800		1	2	56.0	112.1
2SBG5-10	L80*80*8	5450		1	2	52.6	105.3
2SBG5-11	L80*80*8	5350		1	2	51.7	103.4
2SBG5-12	L80*80*8	5800		1	2	56.0	112.1
2SBG5-10X	L50*50*5	1288		2	4	4.9	19.4
2SBG5-11X	L50*50*5	1433		4	8	5.4	43.2
2SBG5-11X	L50*50*5	1433		4	8	5.4	43.2
2SBG5-12X	L50*50*5	1342		13	26	5.1	131.5
2SBG5-12X	L50*50*5	1342		13	26	5.1	131.5
2SBG5-13	L50*50*5	1147		3	6	4.3	25.9
2SBG5-13X	L50*50*5	1147		3	6	4.3	25.9
2SBG5-14	L50*50*5	1254		10	20	4.7	94.6
2SBG5-14X	L50*50*5	1254		10	20	4.7	94.6
2SBG5-15	L50*50*5	1433		6	12	5.4	64.8
2SBG5-15X	L50*50*5	1433		6	12	5.4	64.8
2SBG5-16	L50*50*5	999		3	6	3.8	22.6
2SBG5-16X	L50*50*5	999		3	6	3.8	22.6
2SBG5-17	L50*50*5	1359		7	14	5.1	71.7
2SBG5-17X	L50*50*5	1359		7	14	5.1	71.7
2SBG5-18	L50*50*5	1273		5	10	4.8	48.0
2SBG5-18X	L50*50*5	1273		5	10	4.8	48.0
2SBG5-19	L50*50*5	1571		3	6	5.9	35.5
2SBG5-19X	L50*50*5	1571		3	6	5.9	35.5
2SBG5-20	L50*50*5	1323		3	6	5.0	29.9
2SBG5-20X	L50*50*5	1323		3	6	5.0	29.9
2SBG5-21	L50*50*5	1179		2	4	4.4	17.8
2SBG5-21X	L50*50*5	1179		2	4	4.4	17.8
2SBG5-22	L50*50*5	1473		1	2	5.6	11.1
2SBG5-22X	L50*50*5	1473		1	2	5.6	11.1
2SBG5-23	L50*50*5	1283		2	4	4.8	19.3
2SBG5-23X	L50*50*5	1283		2	4	4.8	19.3
2SBG5-24	L50*50*5	1177		2	4	4.4	17.7
2SBG5-24X	L50*50*5	1177		2	4	4.4	17.7
2SBG5-25	L50*50*5	1239		1	2	4.7	9.3
2SBG5-25X	L50*50*5	1239		1	2	4.7	9.3
2SBG5-26	L50*50*5	1176		2	4	4.4	17.7
2SBG5-26X	L50*50*5	1176		2	4	4.4	17.7
2SBG5-27	L50*50*5	1081		1	2	4.1	8.2
2SBG5-27X	L50*50*5	1081		1	2	4.1	8.2
2SBG5-28	L80*80*8	950		1	2	9.2	18.4
2SBG5-29	L50*50*5	952		1	2	3.6	7.2
2SBG5-29X	L50*50*5	952		1	2	3.6	7.2
2SBG5-30	L50*50*5	466		12	24	1.8	42.2
2SBG5-31	L50*50*5	796		6	12	3.0	36.0
2SBG5-32	PL8	218	139	12	24	1.9	45.7
2SBG5-33	PL10	225	180	8	16	3.2	50.9
2SBG5-34	PL6	375	60	16	32	1.8	56.5
2SBG5-35	PL6	375	60	16	32	1.8	56.5
2SBG5-36	L80*80*8	168		28	56	1.6	90.9
2SBG5-37	UNP160	168		14	28	3.2	88.4
TOTAL WEIGHT (Kg)						3159.6	
WEIGHT						1579.8	

- NOTES
- ALL DIMENSION ARE IN mm.
 - ALL MATERIALS (MEMBERS & BRACES)SHALL BE HOT DIP GALVANIZED AFTER FABRICATION. GALVANIZING THICKNESS FOR STRACTIONS (ACC.TO.ASTM A123)
 - ALL DIMENTIONS AND DISTANCES SHALL BE CHECKED BY MANUFACTURERAND WORK-SHOP DWG. SHOULD BE BASED ON CHECKED VALUE.
 - CUTTING THE FLANGES ARE NOT ACCEPTABLE.
 - ALL PLATES ARE MADE OF MILD STEEL WITH ST 37 (DIN 17100) : $F_y = 2400 \text{ kg/cm}^2$ AND SHOULD BE PROVIDED ACCORDING TO STAHL BOOK.
 - LEG DISTANCES AT BASE OF GENTRY ARE FROM BACK TO BACK OF LEG ANGLES.
 - "S" IS SHIELDWIRE ATTACHMENT POINT TO COLUMN OF GENTRY. SUSPENSION INSULATORS ATTACHMENT POINTS TO BEAM OF GENTRY
 - USE BOLT M16 GRADE 8.8 , $F_u = 8000 \text{ kg/cm}^2$ & $F_y = 6400 \text{ kg/cm}^2$ FOR CONNECTIONS.
 - NUMBER OF BOLTS IN OTHER CONNECTIONS THAT ARE NOT SHOWN IN THIS DRAWING ARE 1*M16 (HOLE $\phi 18$ FOR M16).
 - S.S :SINGLE SHEAR D.S : DOUBLE SHEAR
 - IN ADDITION TO MARKINGS REQUIRED FOR SHIPPING PURPOSES ALL CONTAINERS , BOXES, ETC, SHALL BE MARKED WITH THE FOLLOWING:
 - ANGLE USED IN LEGS , BEAMS AND BRACES UP TO L140 ST37
 - THE COATING OF THE BOLTS , NUTS & WASHERS OF THE CONNECTIONS SHOULD BE OF THE DACROMET TYPE.


00			
REV.	VERIFIED BY:	DATE:	DESCRIPTION
CLIENT:	PROJECT: NORTHERN SITE INTERFACE 400/230 KV SUBSTATION		
Consulting: GHODS NIROO ENGINEERING COMPANY (G.N.E.C)	TITLE: STEEL STRUCTURE FOR COLUMN TYPE "4SBG5"		
	NAME	PROJECT CODE:	COMPUTER NO. :
DESIGNED:	-	-	-
DRAWN:	-	SCALE:	SIZE:
CHECKED:	Z.KH	-	A1
APPROVED:	-		




TOP VIEW



FRONT & BACK VIEW



BOTTOM VIEW



SECTION A-A

SECTION B-B

SECTION C-C


MARK	SIZE	LENGTH	WIDTH	QTY	TOTAL QTY	UNIT W.	TOTAL W.
2SBG1-1	L80*80*8	5950		1	12	57.5	689.7
2SBG1-2	L80*80*8	5450		1	12	52.6	631.8
2SBG1-3	L80*80*8	5200		1	12	50.2	602.8
2SBG1-4	L80*80*8	5950		1	12	57.5	689.7
2SBG1-5	L80*80*8	5500		1	12	53.1	637.6
2SBG1-6	L80*80*8	5200		1	12	50.2	602.8
2SBG1-7	L80*80*8	5950		1	12	57.5	689.7
2SBG1-8	L80*80*8	5450		1	12	52.6	631.8
2SBG1-9	L80*80*8	5200		1	12	50.2	602.8
2SBG1-10	L80*80*8	5950		1	12	57.5	689.7
2SBG1-11	L80*80*8	5450		1	12	52.6	631.8
2SBG1-12	L80*80*8	5200		1	12	50.2	602.8
2SBG1-10	L50*50*5	1288		2	24	4.9	116.5
2SBG1-10X	L50*50*5	1288		2	24	4.9	116.5
2SBG1-11	L50*50*5	1433		8	96	5.4	518.6
2SBG1-11X	L50*50*5	1433		8	96	5.4	518.6
2SBG1-12	L50*50*5	1342		8	96	5.1	485.7
2SBG1-12X	L50*50*5	1342		8	96	5.1	485.7
2SBG1-13	L50*50*5	1147		6	72	4.3	311.3
2SBG1-13X	L50*50*5	1147		6	72	4.3	311.3
2SBG1-14	L50*50*5	1323		30	360	5.0	1795.6
2SBG1-14X	L50*50*5	1323		30	360	5.0	1795.6
2SBG1-15	L50*50*5	1239		10	120	4.7	560.5
2SBG1-15X	L50*50*5	1239		10	120	4.7	560.5
2SBG1-16	L50*50*5	1288		2	24	4.9	116.5
2SBG1-16X	L50*50*5	1288		2	24	4.9	116.5
2SBG1-17	L50*50*5	1273		2	24	4.8	115.2
2SBG1-17X	L50*50*5	1273		2	24	4.8	115.2
2SBG1-18	L50*50*5	1273		2	24	4.8	115.2
2SBG1-18X	L50*50*5	1273		2	24	4.8	115.2
2SBG1-19	L50*50*5	1081		2	24	4.1	97.8
2SBG1-19X	L50*50*5	1081		2	24	4.1	97.8
2SBG1-20	L80*80*8	950		28	336	9.2	3083.5
2SBG1-21	L50*50*5	466		12	144	1.8	253.0
2SBG1-22	L50*50*5	796		6	72	3.0	216.1
2SBG1-23	UNP160	168		9	108	3.2	341.1
2SBG1-24	L80*80*8	168		18	216	1.6	350.5
2SBG1-25	PL10	225	180	8	96	3.2	305.2
2SBG1-26	PL8	218	139	12	144	1.9	274.0
2SBG1-30	PL6	375	60	16	192	1.1	203.5
2SBG1-31	PL6	375	60	16	192	1.1	203.5
FPL8	PL8	50	50	75	900	0.2	141.3
TOTAL WEIGHT (Kg)							21540.6
WEIGHT							1795.0

NOTES


- ALL DIMENTION ARE IN mm.
- ALL MATERIALS (MEMBERS & BRACES ...)SHALL BE HOT DIP GALVANIZED AFTER FABRICATION. GALVANIZING THICKNESS FOR STRUCTURE (ACC.TO.ASTM A123)
- ALL DIMENTIONS AND DISTANSES SHALL BE CHECKED BY MANUFACTURERAND WORK-SHOP DWG. SHOULD BE BASED ON CHECKED VALUE.
- CUTTING THE FLANGE ARE NOT ACCEPTABLE.
- ALL PLATES ARE MADE OF MILD STEEL WITH ST 37 (DIN 17100) : $F_y = 2400 \text{ kg/cm}^2$ AND SHOULD BE PROVIDED ECCORDING TO STAHL BOOK.
- LEG DISTANCES AT BASE OF GANTRY ARE FROM BACK TO BACK OF LEG ANGLES.
- "S" IS SHIELDWIRE ATTACHMENT POINT TO COLUMN OF GANTRY. SUSPENSION INSULATORS ATTACHMENT POINTS TO BEAM OF GANTRY
- USE BOLT M16 GRADE 8.8 $F_u = 8000 \text{ kg/cm}^2$ & $F_y = 6400 \text{ kg/cm}^2$ FOR CONNECTIONS.
- NUMBER OF BOLTS IN OTHER CONNECTIONS THAT ARE NOT SHOWN IN THIS DRAWING ARE 1*M16 (HOLE $\phi 18$ FOR M16).
- S.S :SINGLE SHEAR D.S : DOUBLE SHEAR
- IN ADDITION TO MARKINGS REQUARED FOR SHIPPING PURPOSES ALL CONTAINERS , BOXES, ETC. SHALL BE MARKED WITH THE FOLLOWING:
- ANGLE USED IN LEGS , BEAMS AND BRACES UP TO L140 ST37
- THE COATING OF THE BOLTS , NUTS & WASHERS OF THE CONNECTIONS SHOULD BE OF THE DACROMET TYPE.

00			
REV.	VERIFIED BY:	DATE:	DESCRIPTION
CLIENT:	PROJECT:		
P.G.M.I.S.E.Z	NORTHERN SITE INTERFACE 400/230 KV SUBSTATION		
Consulting:	TITLE:		
GHODS NIROO ENGINEERING COMPANY (G.N.E.C)	STEEL STRUCTURE FOR COLUMN TYPE "2SBG3"		
	NAME	PROJECT CODE:	COMPUTER NO. :
DESIGNED:	-	-	-
DRAWN:	-	SCALE:	SIZE:
CHECKED:	Z.KH	-	A1
APPROVED:	-		DRAWING NO. : -


NO : 12




TOP VIEW



FRONT & BACK VIEW



BOTTOM VIEW



SECTION A-A

SECTION B-B

SECTION C-C


MARK	SIZE	LENGTH	WIDTH	QTY	TOTAL QTY	UNIT W.	TOTAL W.
2SBG1-1	L80*80*8	5950		1	12	57.5	689.7
2SBG1-2	L80*80*8	5450		1	12	52.6	631.8
2SBG1-3	L80*80*8	5200		1	12	50.2	602.8
2SBG1-4	L80*80*8	5950		1	12	57.5	689.7
2SBG1-5	L80*80*8	5500		1	12	53.1	637.6
2SBG1-6	L80*80*8	5200		1	12	50.2	602.8
2SBG1-7	L80*80*8	5950		1	12	57.5	689.7
2SBG1-8	L80*80*8	5450		1	12	52.6	631.8
2SBG1-9	L80*80*8	5200		1	12	50.2	602.8
2SBG1-10	L80*80*8	5950		1	12	57.5	689.7
2SBG1-11	L80*80*8	5450		1	12	52.6	631.8
2SBG1-12	L80*80*8	5200		1	12	50.2	602.8
2SBG1-10	L50*50*5	1288		2	24	4.9	116.5
2SBG1-10X	L50*50*5	1288		2	24	4.9	116.5
2SBG1-11	L50*50*5	1433		8	96	5.4	518.6
2SBG1-11X	L50*50*5	1433		8	96	5.4	518.6
2SBG1-12	L50*50*5	1342		8	96	5.1	485.7
2SBG1-12X	L50*50*5	1342		8	96	5.1	485.7
2SBG1-13	L50*50*5	1147		6	72	4.3	311.3
2SBG1-13X	L50*50*5	1147		6	72	4.3	311.3
2SBG1-14	L50*50*5	1323		30	360	5.0	1795.6
2SBG1-14X	L50*50*5	1323		30	360	5.0	1795.6
2SBG1-15	L50*50*5	1239		10	120	4.7	560.5
2SBG1-15X	L50*50*5	1239		10	120	4.7	560.5
2SBG1-16	L50*50*5	1288		2	24	4.9	116.5
2SBG1-16X	L50*50*5	1288		2	24	4.9	116.5
2SBG1-17	L50*50*5	1273		2	24	4.8	115.2
2SBG1-17X	L50*50*5	1273		2	24	4.8	115.2
2SBG1-18	L50*50*5	1273		2	24	4.8	115.2
2SBG1-18X	L50*50*5	1273		2	24	4.8	115.2
2SBG1-19	L50*50*5	1081		2	24	4.1	97.8
2SBG1-19X	L50*50*5	1081		2	24	4.1	97.8
2SBG1-20	L80*80*8	950		28	336	9.2	3083.5
2SBG1-21	L50*50*5	466		12	144	1.8	253.0
2SBG1-22	L50*50*5	796		6	72	3.0	216.1
2SBG1-23	UNP160	168		9	108	3.2	341.1
2SBG1-24	L80*80*8	168		18	216	1.6	350.5
2SBG1-25	PL10	225	180	8	96	3.2	305.2
2SBG1-26	PL8	218	139	12	144	1.9	274.0
2SBG1-30	PL6	375	60	16	192	1.1	203.5
2SBG1-31	PL6	375	60	16	192	1.1	203.5
FPL8	PL8	50	50	75	900	0.2	141.3
TOTAL WEIGHT (Kg)						21540.6	
WEIGHT						1795.0	

NOTES


- ALL DIMENTION ARE IN mm.
- ALL MATERIALS (MEMBERS & BRACES ...)SHALL BE HOT DIP GALVANIZED AFTER FABRICATION. GALVANIZING THICKNESS FOR STRUCTURE (ACC.TO.ASTM A123)
- ALL DIMENTION AND DISTANSES SHALL BE CHECKED BY MANUFACTURERAND WORK-SHOP DWG. SHOULD BE BASED ON CHECKED VALUE.
- CUTTING THE FLANGE ARE NOT ACCEPTABLE.
- ALL PLATES ARE MADE OF MILD STEEL WITH ST 37 (DIN 17100) : $F_y = 2400 \text{ kg/cm}^2$ AND SHOULD BE PROVIDED ECCRORDING TO STAHL BOOK.
- LEG DISTANCES AT BASE OF GANTRY ARE FROM BACK TO BACK OF LEG ANGLES.
- "S" IS SHIELDWIRE ATTACHMENT POINT TO COLUMN OF GANTRY. SUSPENSION INSULATORS ATTACHMENT POINTS TO BEAM OF GANTRY
- USE BOLT M16 GRADE 8.8 $F_u = 8000 \text{ kg/cm}^2$ & $F_y = 6400 \text{ kg/cm}^2$ FOR CONNECTIONS.
- NUMBER OF BOLTS IN OTHER CONNECTIONS THAT ARE NOT SHOWN IN THIS DRAWING ARE 1*M16 (HOLE $\phi 18$ FOR M16).
- S.S :SINGLE SHEAR D.S : DOUBLE SHEAR
- IN ADDITION TO MARKINGS REQUARED FOR SHIPPING PURPOSES ALL CONTAINERS , BOXES, ETC. SHALL BE MARKED WITH THE FOLLOWING:
- ANGLE USED IN LEGS , BEAMS AND BRACES UP TO L140 ST37
- THE COATING OF THE BOLTS , NUTS & WASHERS OF THE CONNECTIONS SHOULD BE OF THE DACROMET TYPE.

00			
REV.	VERIFIED BY:	DATE:	DESCRIPTION
CLIENT:	PROJECT:		
P.G.M.I.S.E.Z	NORTHERN SITE INTERFACE 400/230 KV SUBSTATION		
Consulting:	TITLE:		
GHODS NIROO ENGINEERING COMPANY (G.N.E.C)	STEEL STRUCTURE FOR COLUMN TYPE "2SBG2"		
	NAME	PROJECT CODE:	COMPUTER NO. :
DESIGNED:	-	-	-
DRAWN:	-	SCALE:	SIZE:
CHECKED:	Z.KH	-	A1
APPROVED:	-		DRAWING NO. : -


NO : 12




TOP VIEW




FRONT & BACK VIEW



BOTTOM VIEW



SECTION A-A




SECTION B-B

MARK	SIZE	LENGTH	WIDTH	QTY	TOTAL QTY	UNIT W.	TOTAL W.
25BG4-1	L80*80*8	5450		1	2	52.6	105.3
25BG4-2	L80*80*8	5350		1	2	51.7	103.4
25BG4-3	L80*80*8	5800		1	2	56.0	112.1
25BG4-4	L80*80*8	5450		1	2	52.6	105.3
25BG4-5	L80*80*8	5350		1	2	51.7	103.4
25BG4-6	L80*80*8	5800		1	2	56.0	112.1
25BG4-7	L80*80*8	5450		1	2	52.6	105.3
25BG4-8	L80*80*8	5350		1	2	51.7	103.4
25BG4-9	L80*80*8	5800		1	2	56.0	112.1
25BG4-10	L80*80*8	5450		1	2	52.6	105.3
25BG4-11	L80*80*8	5350		1	2	51.7	103.4
25BG4-12	L80*80*8	5800		1	2	56.0	112.1
25BG4-10	L50*50*5	1288		2	4	4.9	19.4
25BG4-10X	L50*50*5	1288		2	4	4.9	19.4
25BG4-11	L50*50*5	1433		4	8	5.4	43.2
25BG4-11X	L50*50*5	1433		4	8	5.4	43.2
25BG4-12	L50*50*5	1342		13	26	5.1	131.5
25BG4-12X	L50*50*5	1342		13	26	5.1	131.5
25BG4-13	L50*50*5	1147		3	6	4.3	25.9
25BG4-13X	L50*50*5	1147		3	6	4.3	25.9
25BG4-14	L50*50*5	1254		10	20	4.7	94.6
25BG4-14X	L50*50*5	1254		10	20	4.7	94.6
25BG4-15	L50*50*5	1433		6	12	5.4	64.8
25BG4-15X	L50*50*5	1433		6	12	5.4	64.8
25BG4-16	L50*50*5	999		3	6	3.8	22.6
25BG4-16X	L50*50*5	999		3	6	3.8	22.6
25BG4-17	L50*50*5	1359		7	14	5.1	71.7
25BG4-17X	L50*50*5	1359		7	14	5.1	71.7
25BG4-18	L50*50*5	1273		5	10	4.8	48.0
25BG4-18X	L50*50*5	1273		5	10	4.8	48.0
25BG4-19	L50*50*5	1571		3	6	5.9	35.5
25BG4-19X	L50*50*5	1571		3	6	5.9	35.5
25BG4-20	L50*50*5	1323		3	6	5.0	29.9
25BG4-20X	L50*50*5	1323		3	6	5.0	29.9
25BG4-21	L50*50*5	1179		2	4	4.4	17.8
25BG4-21X	L50*50*5	1179		2	4	4.4	17.8
25BG4-22	L50*50*5	1473		1	2	5.6	11.1
25BG4-22X	L50*50*5	1473		1	2	5.6	11.1
25BG4-23	L50*50*5	1283		2	4	4.8	19.3
25BG4-23X	L50*50*5	1283		2	4	4.8	19.3
25BG4-24	L50*50*5	1177		2	4	4.4	17.7
25BG4-24X	L50*50*5	1177		2	4	4.4	17.7
25BG4-25	L50*50*5	1239		1	2	4.7	9.3
25BG4-25X	L50*50*5	1239		1	2	4.7	9.3
25BG4-26	L50*50*5	1176		2	4	4.4	17.7
25BG4-26X	L50*50*5	1176		2	4	4.4	17.7
25BG4-27	L50*50*5	1081		1	2	4.1	8.2
25BG4-27X	L50*50*5	1081		1	2	4.1	8.2
25BG4-28	L80*80*8	950		34	68	3.6	243.5
25BG4-29	L50*50*5	952		1	2	3.6	7.2
25BG4-29X	L50*50*5	952		1	2	3.6	7.2
25BG4-30	L50*50*5	466		12	24	1.8	42.2
25BG4-31	L50*50*5	796		6	12	3.0	36.0
25BG4-32	PL8	218	139	12	24	1.9	45.7
25BG4-33	PL10	225	180	8	16	3.2	50.9
25BG4-40	PL8	380	150	6	12	3.6	43.0
25BG4-41	PL8	380	150	6	12	3.6	43.0
25BG4-42	PL8	628	156	6	12	6.2	73.8
25BG4-43	PL8	380	156	6	12	3.7	44.7
25BG4-44	PL8	380	153	6	12	3.7	43.8
25BG4-45	PL8	380	153	6	12	3.7	43.8
25BG4-46	PL8	380	153	6	12	3.7	43.8
25BG4-47	PL8	380	150	6	12	3.6	43.0
25BG4-48	PL8	628	156	6	12	6.2	73.8
25BG4-49	PL8	380	150	6	12	3.6	43.0
25BG4-50	PL8	680	162	6	12	6.9	83.0
25BG4-51	PL8	380	149	6	12	3.6	42.7
25BG4-52	PL8	380	152	6	12	3.6	43.5
25BG4-53	PL8	628	152	6	12	6.0	71.9
25BG4-54	PL8	380	150	16	32	3.6	114.5
25BG4-55	PL8	628	158	2	4	6.2	24.9
25BG4-56	PL8	628	158	2	4	6.2	24.9
25BG4-57	PL8	380	155	2	4	3.7	14.8
25BG4-58	PL8	380	155	2	4	3.7	14.8
25BG4-59	PL8	525	150	2	4	4.9	19.8
25BG4-60	PL8	380	150	2	4	3.6	14.3
25BG4-61	PL8	628	150	2	4	5.9	23.7
25BG4-62	PL8	380	150	2	4	3.6	14.3
25BG4-63	PL8	857	152	2	4	8.2	32.7
25BG4-64	PL8	380	152	2	4	3.6	14.5
25BG4-65	PL8	380	152	2	4	3.6	14.5
25BG4-66	PL8	628	152	2	4	6.0	24.0
25BG4-67	PL8	628	152	2	4	6.0	24.0
25BG4-68	PL6	375	60	16	32	1.1	33.9
25BG4-69	PL6	375	60	16	32	1.1	33.9
25BG4-70	UNP160	168		14	28	3.2	88.4
25BG4-71	L80*80*8	168		28	56	1.6	90.9
FPL	PL8	50	50	75	150	0.2	23.6
TOTAL WEIGHT (Kg)							4475.7
WEIGHT							2237.8

- NOTES:
- 1- ALL DIMENSIONS ARE IN mm.
 - 2- ALL MATERIALS (MEMBERS & BRACES) SHALL BE HOT DIP GALVANIZED AFTER FABRICATION. GALVANIZING PROCEEDINGS FOR STRUCTURE (A.C.T.O.A.P.M. AISI).
 - 3- ALL DIMENSIONS AND DISTANCES SHALL BE CHECKED BY MANUFACTURER'S WORK-SHEET SPEC. SHOULD BE BASED ON CHECKED VALUE.
 - 4- CUTTING THE PLATE IS NOT ACCEPTABLE.
 - 5- ALL PLATES ARE MADE OF MILD STEEL WITH ST 37 (EN 1710) : F_y = 235 N/mm² AND SHOULD BE PROVIDED ACCORDING TO STEEL CODE.
 - 6- LAG DISTANCES AT BASE OF GANTRY ARE FROM BACK TO BACK OF LAG ANGLE.
 - 7- "B" IS SHELLWARE ATTACHMENT POINT TO COLUMN OF GANTRY. INSULATION ATTACHMENT POINTS TO BEAM OF GANTRY.
 - 8- USE BOLT M16 GRADE 8.8 F_y=800 N/mm² & F_y=840 N/mm² FOR CONNECTIONS.
 - 9- NUMBER OF BOLTS IN OTHER CONNECTIONS THAT ARE NOT SHOWN IN THIS DRAWING ARE 1" MIN (BOLT #18 FOR M16).
 - 10- 1/8" DOUBLE SHEAR, 1/4" DOUBLE SHEAR.
 - 11- IN ADDITION TO MARKINGS REQUIRED FOR SHIPPING PURPOSES ALL CONTAINERS, BOLTS, ETC. SHALL BE MARKED WITH THE FOLLOWING:
 - 12- ANGLES USED IN LAGS, BEAMS AND BRACES UP TO LAG SPEC.
 - 13- THE COATING OF THE BOLTS, NUTS & WASHERS OF THE CONNECTIONS SHOULD BE OF THE DACHMET TYPE.




00			
REV.	VERIFIED BY:	DATE:	DESCRIPTION
CLIENT:	PROJECT: NORTHERN SITE INTERFACE 400/230 KV SUBSTATION		
Consulting:	TITLE: STEEL STRUCTURE FOR COLUMN TYPE "4SBG4"		
DESIGNED:	NAME	PROJECT CODE:	COMPUTER NO. :
DRAWN:	-	-	-
CHECKED:	Z.H.	SCALE:	SIZE: A1
APPROVED:	-	-	DRAWING NO. : -



NOTES

- 1-- ALL DIMENSION ARE IN mm.
- 2-- ALL MATERIALS (MEMBERS) & STRUCTURES ...SHALL BE HOT DIP GALVANIZED AFTER FABRICATION.
- 3-- GALVANIZING THICKNESS FOR BRACES (ACCSO.ASTM A123)
- 4-- ALL DIMENSIONS AND DISTANCES SHALL BE CHECKED BY MANUFACTURER/WORK-SHOP DWG. SHOULD BE BASED ON CHECKED VALUE
- 5--CUTTING THE FLANGES ARE NOT ACCEPTABLE.
- 6-- ALL PLATES ARE MADE OF MILD STEEL WITH SF 30 (EN 10100) : Fy =240kg/cm² AND SHOULD BE PROVIDED ACCORDING TO
- 7-- LEC DISTANCES AT BASE OF CANTILEY ARE FROM BRACE TO BRACE AT LEC ANGLES.
- 8-- "S" IS SHEDDING ATTACHMENT POINT TO COLUMN OF Gantry.
- 9-- RUSTPROOF INSULATION ATTACHMENT POINTS TO BEAM OF Gantry
- 10-- USE BOLT M16 GRADE 8.8 F_u=900kg/cm² & F_y=640kg/cm² FOR CONNECTIONS.
- 11-- NUMBER OF BOLTS IN OTHER CONNECTIONS THAT ARE NOT SHOWN IN THIS DRAWING ARE 1*16 (HOLE R16 FOR M16).
- 12-- 2.5 DOUBLE SHEAR D.S. DOUBLE SHEAR
- 13-- IN ADDITION TO MARKINGS REQUIRED FOR SHIPPING PURPOSES ALL CONTAINERS, BOXES, ETC. SHALL BE MARKED WITH THE FOLLOWING:
ANGLE BEAM IN LEGS , BEAMS AND BRACES UP TO 1440 ST/ST
14-- THE COATING OF THE BOLTS , NUTS & WASHERS OF THE CONNECTIONS SHOULD BE OF THE DACROMET TYPE.



NO : 4



MARK	SIZE	LENGTH	WIDTH	QTY	TOTAL QTY	UNIT W.	TOTAL W.
2SCG7-1	L140*140*14	1000		2	2	29.4	58.8
2SCG7-2	L140*140*14	1000		2	2	29.4	58.8
2SCG7-3	L140*140*14	3995		2	2	117.5	234.9
2SCG7-4	L140*140*14	3995		2	2	117.5	234.9
2SCG7-5	L140*140*14	5500		2	2	161.7	323.4
2SCG7-6	L140*140*14	5500		2	2	161.7	323.4
2SCG7-7	L120*120*12	3950		2	2	85.3	170.6
2SCG7-8	L120*120*12	3950		2	2	85.3	170.6
2SCG7-9	L100*100*10	4396		2	2	66.4	132.8
2SCG7-10	L100*100*10	4396		2	2	66.4	132.8
2SCG7-11	L80*80*8	4361		2	2	42.1	84.3
2SCG7-12	L80*80*8	4361		2	2	42.1	84.3
2SCG7-15	L60*60*6	2422		2	2	13.1	26.3
2SCG7-15X	L60*60*6	2422		2	2	13.1	26.3
2SCG7-16	L60*60*6	2397		2	2	13.0	26.0
2SCG7-16X	L60*60*6	2397		2	2	13.0	26.0
2SCG7-17	L60*60*6	2312		2	2	12.5	25.1
2SCG7-17X	L60*60*6	2312		2	2	12.5	25.1
2SCG7-18	L60*60*6	2218		2	2	12.0	24.0
2SCG7-18X	L60*60*6	2218		2	2	12.0	24.0
2SCG7-19	L60*60*6	2115		2	2	11.5	22.9
2SCG7-19X	L60*60*6	2115		2	2	11.5	22.9
2SCG7-20	L60*60*6	2052		2	2	11.1	22.2
2SCG7-20X	L60*60*6	2052		2	2	11.1	22.2
2SCG7-21	L60*60*6	1949		2	2	10.6	21.1
2SCG7-21X	L60*60*6	1949		2	2	10.6	21.1
2SCG7-22	L60*60*6	1891		2	2	10.2	20.5
2SCG7-22X	L60*60*6	1891		2	2	10.2	20.5
2SCG7-23	L60*60*6	1865		4	4	10.1	40.4
2SCG7-23X	L60*60*6	1865		4	4	10.1	40.4
2SCG7-24	L80*80*8	950		4	4	9.2	36.7
2SCG7-25	L80*80*8	950		8	8	9.0	71.9
2SCG7-26	L60*60*6	1072		2	2	5.8	11.6
2SCG7-26X	L60*60*6	1072		2	2	5.8	11.6
2SCG7-27	L50*50*5	1631		2	2	8.8	17.7
2SCG7-27X	L50*50*5	1631		2	2	8.8	17.7
2SCG7-28	L60*60*6	732		2	2	4.0	7.9
2SCG7-29	L50*50*5	1581		2	2	6.0	11.9
2SCG7-30	L50*50*5	471		2	2	1.8	3.6
2SCG7-31	L70*70*7	1767		2	2	13.0	26.1
2SCG7-31X	L70*70*7	1767		2	2	9.6	19.2
2SCG7-32	L60*60*6	1780		6	6	9.6	57.9
2SCG7-32X	L60*60*6	1780		6	6	9.6	57.9
2SCG7-33	L60*60*6	1820		2	2	9.9	19.7
2SCG7-33X	L60*60*6	1820		2	2	9.9	19.7
2SCG7-34	L60*60*6	1885		2	2	10.2	20.4
2SCG7-34X	L60*60*6	1885		2	2	10.2	20.4
2SCG7-35	L60*60*6	1910		4	4	10.4	41.4
2SCG7-35X	L60*60*6	1910		4	4	10.4	41.4
2SCG7-36	L60*60*6	1976		4	4	10.7	42.8
2SCG7-36X	L60*60*6	1976		4	4	10.7	42.8
2SCG7-37	L80*80*8	1130		4	4	10.9	43.7
2SCG7-38	L60*60*6	1230		2	2	6.7	13.3
2SCG7-38X	L60*60*6	1230		2	2	6.7	13.3
2SCG7-39	L50*50*5	1715		2	2	6.5	12.9
2SCG7-40	L50*50*5	876		2	2	3.3	6.6
2SCG7-41	L50*50*5	1622		2	2	6.1	12.2
2SCG7-42	L50*50*5	543		2	2	2.0	4.1
2SCG7-43	L60*60*6	1202		2	2	6.5	13.0
2SCG7-43X	L60*60*6	1202		2	2	6.5	13.0
2SCG7-44	PL8	400	220	4	4	5.5	22.1
2SCG7-45	PL8	440	226	4	4	6.2	25.0
2SCG7-46	PL8	409	205	4	4	5.2	20.8
2SCG7-47	PL8	465	224	4	4	6.5	26.2
2SCG7-48	PL8	430	194	4	4	5.2	21.0
2SCG7-49	PL8	450	190	4	4	5.4	21.5
2SCG7-50	PL8	494	190	4	4	5.9	23.6
2SCG7-51	PL8	516	179	4	4	5.8	23.2
2SCG7-52	PL10	500	178	4	4	7.0	27.9
2SCG7-53	PL10	380	178	4	4	5.3	21.2
2SCG7-54	PL10	247	185	2	2	3.6	7.2
2SCG7-55	PL8	603	205	4	4	7.8	31.1
2SCG7-56	PL8	581	205	12	12	7.5	89.8
2SCG7-57	PL8	540	185	4	4	6.3	25.1
2SCG7-58	PL8	490	185	8	8	5.7	45.5
2SCG7-59	PL8	512	189	4	4	6.1	24.3
2SCG7-60	PL10	489	170	4	4	17.7	70.8
2SCG7-61	PL10	470	380	4	4	14.0	56.1
2SCG7-62	PL10	681	185	1	1	9.9	9.9
2SCG7-63	PL10	158	135	8	8	1.7	13.4
2SCG7-72	L60*60*6	844		2	2	4.6	9.1
2SCG7-73	L60*60*6	892		2	2	4.8	9.7
2SCG7-74	PL12	495	110	16	16	5.1	82.1
2SCG7-75	PL12	495	90	8	8	4.2	33.6
2SCG7-76	PL12	465	100	8	8	4.4	35.0
2SCG7-77	PL12	465	80	8	8	3.5	28.0
2SCG7-77F	PL2	230	80	8	8	0.3	2.3
2SCG7-78	PL10	475	90	8	8	3.4	26.8
2SCG7-79	L80*80*8	475		4	4	4.6	18.4
2SCG7-79F	PL2	235	60	8	8	0.2	1.8
2SCG7-90	PL25	420	420	4	4	34.6	138.5
2SCG7-91	PL12	460	300	4	4	13.0	52.0
2SCG7-92	PL12	370	300	4	4	10.5	41.8
2SCG7-93	PL12	300	148	12	12	4.2	50.2
2SCG7-94	PL12	300	148	8	8	4.2	33.5
2SCG7-95	PL12	300	99	4	4	2.8	11.2
2SCG7-96	PL12	300	125	8	8	3.5	28.3
FPL8	PL8	50	50	45	45	0.2	7.1
TOTAL WEIGHT (Kg)						4408.7	
WEIGHT						2204.3	

- NOTES
- 1- ALL DIMENSION ARE IN mm.
 - 2- ALL MATERIALS (MEMBERS & BRACES ...)SHALL BE HOT DIP GALVANIZED AFTER FABRICATION.
 - 3- ALL DIMENSIONS AND DISTANCES SHALL BE CHECKED BY MANUFACTURER AND WORK-SHOP DWG. SHOULD BE BASED ON CHECKED VALUES.
 - 4-CUTTING THE PLATES ARE NOT ACCEPTABLE.
 - 5-ALL PLATES ARE MADE OF MILD STEEL WITH ST 37 (DIN 17100) ; Fy =2400kg/cm² AND SHOULD BE PROVIDED ACCORDING TO STAIL BOOK.
 - 6- LEG DISTANCES AT BASE OF GANTRY ARE FROM BACK TO BACK OF LEG ANGLES.
 - 7- "S" IS SHERIDWIRE ATTACHMENT POINT TO COLUMN OF GANTRY. SUSPENSION INSULATORS ATTACHMENT POINTS TO BEAM OF GANTRY
 - 8- USE BOLT M16 GRADE 8.8 F_u=8000 kg/cm² & F_y=6400 kg/cm² FOR CONNECTIONS.
 - 9- NUMBER OF BOLTS IN OTHER CONNECTIONS THAT ARE NOT SHOWN IN THIS DRAWING ARE 1"x16 (HOLE Ø16 FOR M16).
 - 10- S.S : SINGLE SHEAR D.S : DOUBLE SHEAR
 - 11- IN ADDITION TO MARKINGS REQUIRED FOR SHIPPING PURPOSES ALL CONTAINERS , BOXES, ETC. SHALL BE MARKED WITH THE FOLLOWING:
 - 12- ANGLE USED IN LEGS , BEAMS AND BRACES UP TO L140 ST37
 - 13- THE COATING OF THE BOLTS , NUTS & WASHERS OF THE CONNECTIONS SHOULD BE OF THE DACROMET TYPE.


00	-		
REV.	VERIFIED BY:	DATE:	DESCRIPTION
CLIENT:		PROJECT:	NORTHERN SITE INTERFACE 400/230 KV SUBSTATION
Consulting:		TITLE:	STEEL STRUCTURE FOR COLUMN TYPE "2SCG7"
DESIGNED:	NAME	PROJECT CODE:	COMPUTER NO. :
DRAWN:	-	-	-
CHECKED:	Z.KH	SCALE:	SIZE: A1
APPROVED:	-	-	-




MARK	SIZE	LENGTH	WIDTH	QTY	TOTAL QTY	UNIT W.	TOTAL W.
2SCG6-1	L120*120*12	1000		2	4	21.6	86.4
2SCG6-2	L120*120*12	1000		2	4	21.6	86.4
2SCG6-3	L120*120*12	1995		2	4	43.1	172.4
2SCG6-4	L120*120*12	1995		2	4	43.1	172.4
2SCG6-5	L120*120*12	3950		2	4	85.3	341.3
2SCG6-6	L120*120*12	3950		2	4	85.3	341.3
2SCG6-7	L120*120*12	5950		2	4	128.5	514.1
2SCG6-8	L120*120*12	5950		2	4	128.5	514.1
2SCG6-9	L100*100*10	5946		2	4	89.8	359.1
2SCG6-10	L100*100*10	5946		2	4	89.8	359.1
2SCG6-11	L80*80*8	4361		2	4	42.1	168.5
2SCG6-12	L80*80*8	4361		2	4	42.1	168.5
2SCG6-15	L60*60*6	2447		4	8	13.3	106.1
2SCG6-15X	L60*60*6	2447		4	8	13.3	106.1
2SCG6-16	L60*60*6	2342		2	4	12.7	50.8
2SCG6-16X	L60*60*6	2342		2	4	12.7	50.8
2SCG6-17	L60*60*6	2238		2	4	12.1	48.5
2SCG6-17X	L60*60*6	2238		2	4	12.1	48.5
2SCG6-18	L60*60*6	2150		2	4	11.7	46.6
2SCG6-18X	L60*60*6	2150		2	4	11.7	46.6
2SCG6-19	L60*60*6	2082		2	4	11.3	45.1
2SCG6-19X	L60*60*6	2082		2	4	11.3	45.1
2SCG6-20	L60*60*6	2009		2	4	10.9	43.6
2SCG6-20X	L60*60*6	2009		2	4	10.9	43.6
2SCG6-21	L60*60*6	1931		2	4	10.5	41.9
2SCG6-21X	L60*60*6	1931		2	4	10.5	41.9
2SCG6-22	L60*60*6	1863		2	4	10.1	40.4
2SCG6-22X	L60*60*6	1863		2	4	10.1	40.4
2SCG6-23	L80*80*8	930		4	8	9.0	71.9
2SCG6-24	L80*80*8	930		4	8	9.2	76.7
2SCG6-25	L60*60*6	1073		2	4	5.8	23.3
2SCG6-25X	L60*60*6	1073		2	4	5.8	23.3
2SCG6-26	L60*60*6	1631		2	4	8.8	35.4
2SCG6-27	L50*50*5	731		2	4	2.8	11.0
2SCG6-28	L50*50*5	1581		2	4	8.6	34.3
2SCG6-29	L50*50*5	471		2	4	1.8	7.1
2SCG6-30	L60*60*6	1816		2	4	9.8	39.4
2SCG6-30X	L60*60*6	1816		2	4	9.8	39.4
2SCG6-31	L60*60*6	1860		8	16	10.1	161.3
2SCG6-31X	L60*60*6	1860		8	16	10.1	161.3
2SCG6-32	L60*60*6	1885		2	4	10.2	40.9
2SCG6-32X	L60*60*6	1885		2	4	10.2	40.9
2SCG6-33	L60*60*6	1910		4	8	10.4	82.8
2SCG6-33X	L60*60*6	1910		4	8	10.4	82.8
2SCG6-34	L60*60*6	1976		2	4	10.7	42.8
2SCG6-34X	L60*60*6	1976		2	4	10.7	42.8
2SCG6-35	L80*80*8	1130		4	8	10.9	87.3
2SCG6-36	L80*80*8	1230		2	4	11.9	47.5
2SCG6-36X	L80*80*8	1230		2	4	11.9	47.5
2SCG6-36Z	L60*60*6	1715		2	4	9.3	37.2
2SCG6-37	L50*50*5	876		2	4	3.3	13.2
2SCG6-38	L60*60*6	1622		2	4	8.8	35.2
2SCG6-39	L50*50*5	543		2	4	2.0	8.2
2SCG6-40	L60*60*6	1202		2	4	6.5	26.1
2SCG6-40X	L60*60*6	1202		2	4	6.5	26.1
2SCG6-41	PL8	400	200	4	8	5.0	40.2
2SCG6-42	PL8	400	206	4	8	5.2	41.4
2SCG6-43	PL8	40	205	4	8	0.5	4.1
2SCG6-44	PL8	416	204	4	8	5.3	42.6
2SCG6-45	PL8	430	194	4	8	5.2	41.9
2SCG6-46	PL8	416	172	4	8	4.5	35.9
2SCG6-47	PL8	442	179	4	8	5.0	39.7
2SCG6-48	PL8	470	167	4	8	4.9	39.4
2SCG6-49	PL10	455	178	4	8	6.4	50.9
2SCG6-50	PL10	380	178	4	8	5.3	42.5
2SCG6-51	PL10	247	185	2	4	3.6	14.3
2SCG6-52	PL8	540	185	4	8	6.3	50.2
2SCG6-53	PL8	540	185	16	32	6.3	200.8
2SCG6-54	PL8	490	185	8	16	5.7	91.1
2SCG6-55	PL8	490	185	4	8	5.7	45.5
2SCG6-56	PL10	455	224	2	4	8.0	32.0
2SCG6-57	PL10	380	224	2	4	6.7	26.7
2SCG6-58	PL10	508	455	2	4	18.1	72.6
2SCG6-59	PL10	509	380	2	4	15.2	60.7
2SCG6-60	PL10	681	165	1	2	9.9	19.8
2SCG6-61	PL8	188	133	8	16	1.3	21.4
2SCG6-70	PL8	500	100	1	2	3.1	6.3
2SCG6-71	UNR120	90		2	4	0.7	2.7
2SCG6-72	L60*60*6	844		2	4	4.6	18.3
2SCG6-73	L60*60*6	892		2	4	4.8	19.3
2SCG6-74	PL10	425	110	8	16	3.7	58.7
2SCG6-75	L100*100*10	425		4	8	6.4	51.3
2SCG6-76	PL10	485	90	16	32	3.4	109.6
2SCG6-77	L100*100*10	485		8	16	7.3	117.2
2SCG6-78	PL10	475	90	8	16	3.4	53.7
2SCG6-79	L80*80*8	475		4	8	4.6	36.7
2SCG6-79F	PL2	235	60	8	16	0.2	3.5
2SCG6-90	PL25	420	420	4	8	34.6	276.9
2SCG6-91	PL12	460	300	4	8	13.0	104.0
2SCG6-92	PL12	370	300	4	8	10.5	83.6
2SCG6-93	PL12	300	148	12	24	4.2	100.4
2SCG6-94	PL12	300	148	8	16	4.2	66.9
2SCG6-95	PL12	300	99	4	8	2.8	22.4
2SCG6-96	PL12	300	125	8	16	3.5	56.5
FPL8	PL8	50	50	45	90	0.2	21.2
TOTAL WEIGHT (Kg)						7658.3	
WEIGHT						3829.1	

- NOTES
- 1- ALL DIMENSION ARE IN mm.
 - 2- ALL MATERIALS (MEMBERS & BRACES ...)SHALL BE HOT DIP GALVANIZED AFTER FABRICATION. GALVANIZING THICKNESS FOR STRUCTURE (ACCTOASTM A183)
 - 3- ALL DIMENSIONS AND DISTANCES SHALL BE CHECKED BY MANUFACTURERAND WORK-SHOP DWG. SHOULD BE BASED ON CHECKED VALUE.
 - 4-CUTTING THE FLANGES ARE NOT ACCEPTABLE.
 - 5-ALL PLATES ARE MADE OF MILD STEEL WITH ST 57 (DIN 17100) ; $F_y = 240\text{N/mm}^2$ AND SHOULD BE PROVIDED ACCORDING TO STEEL BOOK.
 - 6- LEG DISTANCES AT BASE OF GANTRY ARE FROM BACK TO BACK OF LEG ANGLES.
 - 7- "S" IS SHIELDWIRE ATTACHMENT POINT TO COLUMN OF GANTRY. SUSPENSION INSULATORS ATTACHMENT POINTS TO BEAM OF GANTRY
 - 8- USE BOLT M16 GRADE 8.8 $F_u=800\text{N/mm}^2$ & $F_y=640\text{N/mm}^2$ FOR CONNECTIONS.
 - 9- NUMBER OF BOLTS IN OTHER CONNECTIONS THAT ARE NOT SHOWN IN THIS DRAWING ARE "M16 (HOLE Ø18 FOR M16).
 - 10- S.S : SINGLE SHEAR D.S : DOUBLE SHEAR
 - 11- IN ADDITION TO MARKINGS REQUIRED FOR SHIPPING PURPOSES ALL CONTAINERS , BOXES, ETC. SHALL BE MARKED WITH THE FOLLOWING:
 - 12- ANGLE USED IN LEGS , BEAMS AND BRACES UP TO L140 ST37
 - 13- THE COATING OF THE BOLTS , NUTS & WASHERS OF THE CONNECTIONS SHOULD BE OF THE DACTON TYPE.

00	-		
REV.	VERIFIED BY:	DATE:	DESCRIPTION
CLIENT:		PROJECT:	NORTHERN SITE INTERFACE 400/230 KV SUBSTATION
Consulting:		TITLE:	STEEL STRUCTURE FOR COLUMN TYPE "2SCG6"
DESIGNED:	-	PROJECT CODE:	COMPUTER NO. :
DRAWN:	-	SCALE:	DRAWING NO. :
CHECKED:	Z.KH	SIZE:	A1
APPROVED:	-		



SIDE VIEW




FRONT VIEW

MARK	SIZE	LENGTH	WIDTH	QTY	TOTAL QTY	UNIT W.	TOTAL W.
2SCG5-1	L140*140*14	1000		2	4	29.4	117.6
2SCG5-2	L140*140*14	1000		2	4	29.4	117.6
2SCG5-3	L140*140*14	3995		2	4	117.5	469.8
2SCG5-4	L140*140*14	3995		2	4	117.5	469.8
2SCG5-5	L140*140*14	5500		2	4	161.7	646.8
2SCG5-6	L140*140*14	5500		2	4	161.7	646.8
2SCG5-7	L120*120*12	3950		2	4	85.3	341.3
2SCG5-8	L120*120*12	3950		2	4	85.3	341.3
2SCG5-9	L100*100*10	4396		2	4	66.4	265.5
2SCG5-10	L100*100*10	4396		2	4	66.4	265.5
2SCG5-11	L80*80*8	4361		2	4	42.1	168.5
2SCG5-12	L80*80*8	4361		2	4	42.1	168.5
2SCG5-15	L60*60*6	2422		2	4	13.1	52.5
2SCG5-15X	L60*60*6	2422		2	4	13.1	52.5
2SCG5-16	L60*60*6	2397		2	4	13.0	52.0
2SCG5-16X	L60*60*6	2397		2	4	13.0	52.0
2SCG5-17	L60*60*6	2312		2	4	12.5	50.1
2SCG5-17X	L60*60*6	2312		2	4	12.5	50.1
2SCG5-18	L60*60*6	2218		2	4	12.0	48.1
2SCG5-18X	L60*60*6	2218		2	4	12.0	48.1
2SCG5-19	L60*60*6	2115		2	4	11.5	45.9
2SCG5-19X	L60*60*6	2115		2	4	11.5	45.9
2SCG5-20	L60*60*6	2052		2	4	11.1	44.5
2SCG5-20X	L60*60*6	2052		2	4	11.1	44.5
2SCG5-21	L60*60*6	1949		2	4	10.6	42.3
2SCG5-21X	L60*60*6	1949		2	4	10.6	42.3
2SCG5-22	L60*60*6	1891		2	4	10.2	41.0
2SCG5-22X	L60*60*6	1891		2	4	10.2	41.0
2SCG5-23	L60*60*6	1863		4	8	10.1	80.8
2SCG5-23X	L60*60*6	1863		4	8	10.1	80.8
2SCG5-24	L80*80*8	950		4	8	9.2	73.4
2SCG5-25	L80*80*8	930		8	16	9.0	143.7
2SCG5-26	L60*60*6	1073		2	4	5.8	23.3
2SCG5-26X	L60*60*6	1073		2	4	5.8	23.3
2SCG5-27	L50*50*5	1631		2	4	8.8	35.4
2SCG5-27X	L50*50*5	1631		2	4	8.8	35.4
2SCG5-28	L60*60*6	732		2	4	4.0	15.9
2SCG5-29	L50*50*5	1581		2	4	6.0	23.8
2SCG5-29X	L50*50*5	1581		2	4	6.0	23.8
2SCG5-30	L50*50*5	471		2	4	1.8	7.1
2SCG5-31	L70*70*7	1767		2	4	13.0	52.2
2SCG5-31X	L70*70*7	1767		2	4	9.6	38.3
2SCG5-32	L60*60*6	1780		6	12	9.6	115.8
2SCG5-32X	L60*60*6	1780		6	12	9.6	115.8
2SCG5-33	L60*60*6	1820		2	4	9.9	39.5
2SCG5-33X	L60*60*6	1820		2	4	9.9	39.5
2SCG5-34	L60*60*6	1885		2	4	10.2	40.9
2SCG5-34X	L60*60*6	1885		2	4	10.2	40.9
2SCG5-35	L60*60*6	1910		4	8	10.4	82.8
2SCG5-35X	L60*60*6	1910		4	8	10.4	82.8
2SCG5-36	L60*60*6	1976		4	8	10.7	85.7
2SCG5-36X	L60*60*6	1976		4	8	10.7	85.7
2SCG5-37	L80*80*8	1130		4	8	10.9	87.3
2SCG5-37X	L80*80*8	1130		2	4	6.7	26.7
2SCG5-38X	L60*60*6	1230		2	4	6.7	26.7
2SCG5-39	L50*50*5	1715		2	4	6.5	25.9
2SCG5-40	L50*50*5	876		2	4	3.3	13.2
2SCG5-41	L50*50*5	1622		2	4	6.1	24.5
2SCG5-42	L50*50*5	543		2	4	2.0	8.2
2SCG5-43	L60*60*6	1202		2	4	6.5	26.1
2SCG5-43X	L60*60*6	1202		2	4	6.5	26.1
2SCG5-44	PL8	400	220	4	8	5.5	44.2
2SCG5-45	PL8	440	226	4	8	6.2	50.0
2SCG5-46	PL8	403	205	4	8	5.2	41.5
2SCG5-47	PL8	465	224	4	8	6.5	52.3
2SCG5-48	PL8	430	194	4	8	5.2	41.9
2SCG5-49	PL8	450	190	4	8	5.4	43.0
2SCG5-50	PL8	494	190	4	8	5.9	47.2
2SCG5-51	PL8	516	179	4	8	5.8	46.4
2SCG5-52	PL10	500	178	4	8	7.0	55.9
2SCG5-53	PL10	380	178	4	8	5.3	42.5
2SCG5-54	PL10	247	185	2	4	3.6	14.3
2SCG5-55	PL8	603	205	4	8	7.8	62.1
2SCG5-56	PL8	581	205	12	24	7.5	179.5
2SCG5-57	PL8	540	185	4	8	6.3	50.2
2SCG5-58	PL8	490	185	8	16	5.7	51.1
2SCG5-59	PL8	512	189	4	8	6.1	48.6
2SCG5-60	PL10	480	470	4	8	17.7	141.7
2SCG5-61	PL10	470	380	4	8	14.0	112.2
2SCG5-62	PL10	681	185	1	2	9.9	49.8
2SCG5-63	PL10	158	135	8	16	1.7	26.8
2SCG5-72	L60*60*6	844		2	4	4.6	18.3
2SCG5-73	L60*60*6	892		2	4	4.8	19.3
2SCG5-74	PL12	495	110	16	32	5.1	164.1
2SCG5-75	PL12	495	90	8	16	4.2	67.1
2SCG5-76	PL12	465	100	8	16	4.4	70.1
2SCG5-77	PL12	465	80	8	16	3.5	56.1
2SCG5-77E	PL2	230	80	8	16	0.3	4.6
2SCG5-78	PL10	475	90	8	16	3.4	53.7
2SCG5-79	L80*80*8	475		4	8	4.6	36.7
2SCG5-79E	PL2	235	60	8	16	0.2	3.5
2SCG5-90	PL25	420	420	4	8	34.6	276.9
2SCG5-91	PL12	460	300	4	8	13.0	104.0
2SCG5-92	PL12	370	300	4	8	10.5	83.6
2SCG5-93	PL12	300	148	12	24	4.2	100.4
2SCG5-94	PL12	300	148	8	16	4.2	66.9
2SCG5-95	PL12	300	99	4	8	2.8	22.4
2SCG5-96	PL12	300	125	8	16	3.5	56.5
FPL8	PL8	50	50	45	90	0.2	14.1
							8817.4
							4408.7

- NOTES
- 1- ALL DIMENSION ARE IN mm.
 - 2- ALL MATERIALS (MEMBERS & BRACES ...)SHALL BE HOT DIP GALVANIZED AFTER FABRICATION.
 - 3- ALL DIMENSIONS AND DISTANCES SHALL BE CHECKED BY MANUFACTURE/REPAIR WORK-SHOP PWC. SHOULD BE BASED ON CHECKED VALUE.
 - 4-CUTTING THE FLANGES ARE NOT ACCEPTABLE.
 - 5-ALL PLATES ARE MADE OF MILD STEEL WITH ST 37 (DIN 17100) : $F_y = 2400 \text{ kg/cm}^2$ AND SHOULD BE PROVIDED ACCORDING TO STAHL BOOK.
 - 6- LEG DISTANCES AT BASE OF GANTRY ARE FROM BACK TO BACK OF LEG ANGLES.
 - 7- "S" IS SHIELDWIRE ATTACHMENT POINT TO COLUMN OF GANTRY.
 - 8- SUSPENSION INSULATORS ATTACHMENT POINTS TO BEAM OF GANTRY.
 - 9- USE BOLT M16 GRADE 8.8 $F_u = 8000 \text{ kg/cm}^2$ & $F_y = 6400 \text{ kg/cm}^2$ FOR CONNECTIONS.
 - 10- NUMBER OF BOLTS IN OTHER CONNECTIONS THAT ARE NOT SHOWN IN THIS DRAWING ARE 1*M16 (HOLE $\phi 18$ FOR M16).
 - 11- IN ADDITION TO MARKINGS REQUIRED FOR SHIPPING PURPOSES ALL CONTAINERS , BOLTS, ETC. SHALL BE MARKED WITH THE FOLLOWING:
 - 12- ANGLE USED IN LEGS , BEAMS AND BRACES UP TO L140 ST37
 - 13- THE COATING OF THE BOLTS , NUTS & WASHERS OF THE CONNECTIONS SHOULD BE OF THE DACTROMET TYPE.

REV.	VERIFIED BY:	DATE:	DESCRIPTION
00			
CLIENT:	PROJECT:		
P.G.M.I.S.E.Z	NORTHERN SITE INTERPHASE 400/230 kV SUBSTATION		
CONTRIBUTING:	TITLE:		
CHIEF ENGINEER (E.C.E.C)	STEEL STRUCTURE FOR COLUMN TYPE "2SCG5"		
DESIGNED:	NAME	PROJECT CODE:	COMPUTER NO. :
DRAWN:			
CHECKED:	Z.K.H	SCALE:	A1
APPROVED:			






MARK	SIZE	LENGTH	WIDTH	QTY	TOTAL QTY	UNIT W.	TOTAL W.
2SCG2-1	L140*140*14	1000		2	12	29.4	352.8
2SCG2-2	L140*140*14	1000		2	12	29.4	352.8
2SCG2-3	L140*140*14	3995		2	12	117.5	1409.4
2SCG2-4	L140*140*14	3995		2	12	117.5	1409.4
2SCG2-5	L140*140*14	3500		2	12	102.9	1234.8
2SCG2-6	L140*140*14	3500		2	12	102.9	1234.8
2SCG2-7	L120*120*12	5950		2	12	128.5	1542.2
2SCG2-8	L120*120*12	5950		2	12	128.5	1542.2
2SCG2-9	L100*100*10	4396		2	12	66.4	796.6
2SCG2-10	L100*100*10	4396		2	12	66.4	796.6
2SCG2-11	L80*80*8	4361		2	12	42.1	505.5
2SCG2-12	L80*80*8	4361		2	12	42.1	505.5
2SCG2-15	L60*60*6	2422		2	12	13.1	157.5
2SCG2-15X	L60*60*6	2422		2	12	13.1	157.5
2SCG2-16	L60*60*6	2397		2	12	13.0	155.9
2SCG2-16X	L60*60*6	2397		2	12	13.0	155.9
2SCG2-17	L60*60*6	2312		2	12	12.5	150.4
2SCG2-17X	L60*60*6	2312		2	12	12.5	150.4
2SCG2-18	L60*60*6	2218		2	12	12.0	144.3
2SCG2-18X	L60*60*6	2218		2	12	12.0	144.3
2SCG2-19	L60*60*6	2115		2	12	11.5	137.6
2SCG2-19X	L60*60*6	2115		2	12	11.5	137.6
2SCG2-20	L60*60*6	2052		2	12	11.1	133.5
2SCG2-20X	L60*60*6	2052		2	12	11.1	133.5
2SCG2-21	L60*60*6	1949		2	12	10.6	126.8
2SCG2-21X	L60*60*6	1949		2	12	10.6	126.8
2SCG2-22	L60*60*6	1891		2	12	10.2	123.0
2SCG2-22X	L60*60*6	1891		2	12	10.2	123.0
2SCG2-23	L60*60*6	1865	4	24	10.1	242.3	
2SCG2-23X	L60*60*6	1865	4	24	10.1	242.3	
2SCG2-24	L80*80*8	950	4	24	9.2	220.2	
2SCG2-25	L80*80*8	950	4	24	9.2	220.2	
2SCG2-26	L60*60*6	1072	2	12	5.8	69.6	
2SCG2-26X	L60*60*6	1072	2	12	5.8	69.6	
2SCG2-26	L60*60*6	1631	2	12	8.8	106.1	
2SCG2-27	L50*50*5	1631	2	12	6.1	73.8	
2SCG2-28	L60*60*6	732	2	12	4.0	47.6	
2SCG2-29	L50*50*5	1581	2	12	6.0	71.5	
2SCG2-30	L50*50*5	471	2	12	1.8	21.3	
2SCG2-31	L60*60*6	1767	2	12	9.6	114.9	
2SCG2-31X	L60*60*6	1767	2	12	9.6	114.9	
2SCG2-32	L60*60*6	1780	6	36	9.6	347.3	
2SCG2-32X	L60*60*6	1780	6	36	9.6	347.3	
2SCG2-33	L60*60*6	1820	2	12	9.9	118.4	
2SCG2-33X	L60*60*6	1820	2	12	9.9	118.4	
2SCG2-34	L60*60*6	1885	2	12	10.2	122.6	
2SCG2-34X	L60*60*6	1885	2	12	10.2	122.6	
2SCG2-35	L60*60*6	1910	4	24	10.4	248.5	
2SCG2-35X	L60*60*6	1910	4	24	10.4	248.5	
2SCG2-36	L60*60*6	1976	4	24	10.7	257.0	
2SCG2-36X	L60*60*6	1976	4	24	10.7	257.0	
2SCG2-37	L80*80*8	1130	4	24	10.9	262.0	
2SCG2-38	L60*60*6	1230	2	12	6.7	80.0	
2SCG2-38X	L60*60*6	1230	2	12	6.7	80.0	
2SCG2-39	L50*50*5	1715	2	12	6.5	77.6	
2SCG2-40	L50*50*5	876	2	12	3.3	39.6	
2SCG2-41	L50*50*5	1622	2	12	6.1	73.4	
2SCG2-42	L50*50*5	543	2	12	2.0	24.6	
2SCG2-43	L60*60*6	1202	2	12	6.5	78.2	
2SCG2-43X	L60*60*6	1202	2	12	6.5	78.2	
2SCG2-44	PL8	400	220	4	24	5.5	132.6
2SCG2-45	PL8	440	226	4	24	6.2	149.9
2SCG2-46	PL8	408	205	4	24	5.2	124.5
2SCG2-47	PL8	465	224	4	24	6.5	157.0
2SCG2-48	PL8	430	194	4	24	5.2	125.7
2SCG2-49	PL8	450	190	4	24	5.4	128.9
2SCG2-50	PL8	494	190	4	24	5.9	141.5
2SCG2-51	PL8	516	179	4	24	5.8	139.2
2SCG2-52	PL10	500	178	4	24	7.0	167.7
2SCG2-53	PL10	380	178	4	24	5.3	127.4
2SCG2-54	PL10	247	185	2	12	3.6	43.0
2SCG2-55	PL8	603	205	4	24	7.8	186.3
2SCG2-56	PL8	581	205	12	72	7.5	538.5
2SCG2-57	PL8	540	185	4	24	6.3	150.6
2SCG2-58	PL8	490	185	8	48	5.7	273.3
2SCG2-59	PL8	512	189	4	24	6.1	145.8
2SCG2-60	PL10	489	470	4	24	17.7	425.0
2SCG2-61	PL10	470	380	4	24	14.0	336.5
2SCG2-62	PL10	581	185	1	6	9.9	59.3
2SCG2-63	PL10	158	135	8	48	1.7	80.4
2SCG2-72	L60*60*6	844	2	12	4.6	54.9	
2SCG2-73	L60*60*6	892	2	12	4.8	58.0	
2SCG2-74	PL12	495	110	16	96	5.1	492.4
2SCG2-75	PL12	495	90	8	48	4.2	201.4
2SCG2-76	PL12	465	100	8	48	4.4	210.3
2SCG2-77	PL12	465	80	8	48	3.5	168.2
2SCG2-77F	PL2	230	80	8	48	0.3	13.9
2SCG2-77F	PL10	475	90	8	48	3.4	161.1
2SCG2-79	L80*80*8	475	4	24	4.6	110.1	
2SCG2-79F	PL2	235	60	8	48	0.2	10.6
2SCG2-90	PL25	420	420	4	24	34.6	830.8
2SCG2-91	PL12	460	300	4	24	13.0	312.0
2SCG2-92	PL12	370	300	4	24	10.5	250.9
2SCG2-93	PL12	300	148	12	72	4.2	301.1
2SCG2-94	PL12	300	148	8	48	4.2	200.8
2SCG2-95	PL12	300	99	4	24	2.8	67.1
2SCG2-96	PL12	300	125	8	48	3.5	169.6
FPL8	PL8	50	50	45	270	0.2	42.4
TOTAL WEIGHT (Kg)						26096.2	
WEIGHT						4399.4	


- NOTES
- 1- ALL DIMENSION ARE IN mm.
 - 2- ALL MATERIALS (MEMBERS & BRACES ...) SHALL BE HOT DIP GALVANIZED AFTER FABRICATION.
 - 3- ALL DIMENSIONS AND DISTANCES SHALL BE CHECKED BY MANUFACTURER AND WORK-SHOP DWG. SHOULD BE BASED ON CHECKED VALUE.
 - 4- CUTTING THE PLATES ARE NOT ACCEPTABLE.
 - 5- ALL PLATES ARE MADE OF MILD STEEL WITH ST 37 (DIN 17100) ; $F_y = 24000 \text{ kg/cm}^2$ AND SHOULD BE PROVIDED ACCORDING TO STEEL BOOK.
 - 6- LEG DISTANCES AT BASE OF GANTRY ARE FROM BACK TO BACK OF LEG ANGLES.
 - 7- "S" IS SHORLWIRE ATTACHMENT POINT TO COLUMN OF GANTRY. SUSPENSION INSULATORS ATTACHMENT POINTS TO BEAM OF GANTRY.
 - 8- USE BOLT M16 GRADE 8.8 $F_u = 8000 \text{ kg/cm}^2$ & $F_y = 6400 \text{ kg/cm}^2$ FOR CONNECTIONS.
 - 9- NUMBER OF BOLTS IN OTHER CONNECTIONS THAT ARE NOT SHOWN IN THIS DRAWING ARE 1"x16 (HOLE $\phi 16$ FOR M16).
 - 10- S.S : SINGLE SHEAR ; D.S : DOUBLE SHEAR
 - 11- IN ADDITION TO MARKINGS REQUIRED FOR SHIPPING PURPOSES ALL CONTAINERS , BOXES , ETC. SHALL BE MARKED WITH THE FOLLOWING:
 - 12- ANGLE USED IN LEGS , BEAMS AND BRACES UP TO L140 ST37
 - 13- THE COATING OF THE BOLTS , NUTS & WASHERS OF THE CONNECTIONS SHOULD BE OF THE DACTONITE TYPE.

REV.	00	VERIFIED BY:	DATE:	DESCRIPTION
CLIENT:	P.G.M.I.S.E.Z			
PROJECT:	NORTHERN SITE INTERFACE 400/230 KV SUBSTATION			
CONTRACTING:	ENGINEERING COMPANY (S.K.E.C.)			
TITLE:	STEEL STRUCTURE FOR COLUMN TYPE "2SCG2"			
DESIGNED:	NAME	PROJECT CODE:	COMPUTER NO. :	
DRAWN:		SCALE:	DRAWING NO. :	
CHECKED:	Z.A.		A1	
APPROVED:				


NO : 6



SECTION A-A



SECTION B-B



SECTION B-B

- NOTES
- 1- ALL DIMENSION ARE IN MM.
 - 2- ALL MATERIALS (MEMBERS & BRACES ...) SHALL BE HOT DIP GALVANIZED AFTER FABRICATION.
 - 3- ALL DIMENSIONS AND DISTANCES SHALL BE CHECKED BY MANUFACTURER AND WORK-SHOP DWG. SHOULD BE BASED ON CHECKED VALUE.
 - 4- CUTTING THE FLANGES ARE NOT ACCEPTABLE.
 - 5- ALL PLATES ARE MADE OF MILD STEEL WITH ST 37 (DIN 17100) : $P_y = 2400 \text{ kg/cm}^2$ AND SHOULD BE PROVIDED ACCORDING TO STAHL BOOK.
 - 6- LEG DISTANCES AT BASE OF GANTRY ARE FROM BACK TO BACK OF LEG ANGLE.
 - 7- "s" IS SHIELDWIRE ATTACHMENT POINT TO COLUMN OF GANTRY.
 - 8- SUSPENSION INSULATORS ATTACHMENT POINTS TO BEAM OF GANTRY.
 - 9- USE BOLT M16 GRADE 8.8 $P_u = 8000 \text{ kg/cm}^2$ & $P_y = 6400 \text{ kg/cm}^2$ FOR CONNECTIONS.
 - 10- NUMBER OF BOLTS IN OTHER CONNECTIONS THAT ARE NOT SHOWN IN THIS DRAWING ARE 1 M16 (HOLE $\phi 18$ FOR M16).
 - 11- S.S : SINGLE SHEAR D.S : DOUBLE SHEAR
 - 12- IN ADDITION TO MARKINGS REQUIRED FOR SHIPPING PURPOSES ALL CONTAINERS, BOXES, ETC. SHALL BE MARKED WITH THE FOLLOWING:
 - 13- THE COATING OF THE BOLTS, NUTS & WASHERS OF THE CONNECTIONS SHOULD BE OF THE DACTROMET TYPE.

MARK	SIZE	LENGTH	WIDTH	QTY	TOTAL QTY	UNIT W.	TOTAL W.
2SCG4-1	L140*140*14	1000		2	8	29.4	235.2
2SCG4-2	L140*140*14	1000		2	8	29.4	235.2
2SCG4-3	L140*140*14	1995		2	8	58.7	469.2
2SCG4-4	L140*140*14	1995		2	8	58.7	469.2
2SCG4-5	L120*120*12	4000		2	8	117.6	940.8
2SCG4-6	L120*120*12	4000		2	8	117.6	940.8
2SCG4-7	L120*120*12	5950		2	8	128.5	1028.2
2SCG4-8	L120*120*12	5950		2	8	128.5	1028.2
2SCG4-9	L100*100*10	5896		2	8	89.0	712.2
2SCG4-10	L100*100*10	5896		2	8	89.0	712.2
2SCG4-11	L80*80*8	4361		2	8	42.1	337.0
2SCG4-12	L80*80*8	4361		2	8	42.1	337.0
2SCG4-15	L60*60*6	2422		2	8	13.1	105.0
2SCG4-15X	L60*60*6	2422		2	8	13.1	105.0
2SCG4-16	L60*60*6	2397		2	8	13.0	103.9
2SCG4-16X	L60*60*6	2397		2	8	13.0	103.9
2SCG4-17	L60*60*6	2312		2	8	12.5	100.2
2SCG4-17X	L60*60*6	2312		2	8	12.5	100.2
2SCG4-18	L60*60*6	2218		2	8	12.0	96.2
2SCG4-18X	L60*60*6	2218		2	8	12.0	96.2
2SCG4-19	L60*60*6	2115		2	8	11.5	91.7
2SCG4-19X	L60*60*6	2115		2	8	11.5	91.7
2SCG4-20	L60*60*6	2052		2	8	11.1	89.0
2SCG4-20X	L60*60*6	2052		2	8	11.1	89.0
2SCG4-21	L60*60*6	1949		2	8	10.6	84.5
2SCG4-21X	L60*60*6	1949		2	8	10.6	84.5
2SCG4-22	L60*60*6	1891		2	8	10.2	82.0
2SCG4-22X	L60*60*6	1891		2	8	10.2	82.0
2SCG4-23	L60*60*6	1863		4	16	10.1	161.6
2SCG4-23X	L60*60*6	1863		4	16	10.1	161.6
2SCG4-24	L80*80*8	900		4	16	9.2	146.8
2SCG4-25	L80*80*8	930		8	32	9.0	287.5
2SCG4-26	L60*60*6	1073		2	8	5.8	46.5
2SCG4-26X	L60*60*6	1073		2	8	5.8	46.5
2SCG4-27	L50*50*5	1631		2	8	8.8	70.7
2SCG4-27X	L50*50*5	1631		2	8	8.8	70.7
2SCG4-28	L50*50*5	1581		2	8	6.1	49.2
2SCG4-29	L50*50*5	1581		2	8	6.1	49.2
2SCG4-30	L50*50*5	1581		2	8	6.1	49.2
2SCG4-31	L70*70*7	1767		2	8	13.0	104.3
2SCG4-31X	L70*70*7	1767		2	8	13.0	104.3
2SCG4-32	L60*60*6	1780		6	24	9.6	231.5
2SCG4-32X	L60*60*6	1780		6	24	9.6	231.5
2SCG4-33	L60*60*6	1820		2	8	9.9	78.9
2SCG4-33X	L60*60*6	1820		2	8	9.9	78.9
2SCG4-34	L60*60*6	1885		2	8	10.2	81.7
2SCG4-34X	L60*60*6	1885		2	8	10.2	81.7
2SCG4-35	L60*60*6	1910		4	16	10.4	165.6
2SCG4-35X	L60*60*6	1910		4	16	10.4	165.6
2SCG4-36	L60*60*6	1976		4	16	10.7	171.4
2SCG4-36X	L60*60*6	1976		4	16	10.7	171.4
2SCG4-37	L80*80*8	1130		4	16	10.9	174.7
2SCG4-38	L60*60*6	1230		2	8	6.7	53.3
2SCG4-38X	L60*60*6	1230		2	8	6.7	53.3
2SCG4-39	L50*50*5	1715		2	8	6.5	51.7
2SCG4-40	L50*50*5	876		2	8	3.3	26.4
2SCG4-41	L50*50*5	1622		2	8	6.1	48.9
2SCG4-42	L50*50*5	543		2	8	2.0	16.4
2SCG4-43	L60*60*6	1202		2	8	6.5	52.1
2SCG4-43X	L60*60*6	1202		2	8	6.5	52.1
2SCG4-44	PL8	400	220	4	16	5.5	88.4
2SCG4-45	PL8	440	226	4	16	6.2	99.9
2SCG4-46	PL8	403	205	4	16	5.2	83.0
2SCG4-47	PL8	465	224	4	16	6.5	104.7
2SCG4-48	PL8	430	194	4	16	5.2	83.8
2SCG4-49	PL8	450	190	4	16	5.4	85.9
2SCG4-50	PL8	494	190	4	16	5.9	94.3
2SCG4-51	PL8	516	179	4	16	5.8	92.8
2SCG4-52	PL10	500	178	4	16	7.0	111.8
2SCG4-53	PL10	380	178	4	16	5.3	85.0
2SCG4-54	PL10	247	185	2	8	3.6	28.7
2SCG4-55	PL8	603	205	4	16	7.8	124.2
2SCG4-56	PL8	581	205	12	48	7.5	359.0
2SCG4-57	PL8	540	185	4	16	6.3	100.4
2SCG4-58	PL8	490	185	8	32	5.7	102.2
2SCG4-59	PL8	512	189	4	16	6.1	97.2
2SCG4-60	PL10	480	470	4	16	17.7	283.4
2SCG4-61	PL10	470	380	4	16	14.0	224.3
2SCG4-62	PL10	681	185	1	4	9.9	39.6
2SCG4-63	PL10	158	135	8	32	1.7	53.6
2SCG4-72	L60*60*6	844		2	8	4.6	36.6
2SCG4-73	L60*60*6	892		2	8	4.8	38.7
2SCG4-74	PL12	495	110	16	64	5.1	328.3
2SCG4-75	PL12	495	90	8	32	4.2	134.3
2SCG4-76	PL12	465	100	8	32	4.4	140.2
2SCG4-77	PL12	465	80	8	32	3.5	112.1
2SCG4-77E	PL2	230	80	8	32	0.3	9.2
2SCG4-78	PL10	475	90	8	32	3.4	107.4
2SCG4-79	L80*80*8	475		4	16	4.6	73.4
2SCG4-79E	PL2	235	60	8	32	0.2	7.1
2SCG4-90	PL25	420	420	4	16	34.6	553.9
2SCG4-91	PL12	460	300	4	16	13.0	208.0
2SCG4-92	PL12	370	300	4	16	10.5	167.3
2SCG4-93	PL12	300	148	12	48	4.2	200.8
2SCG4-94	PL12	300	148	8	32	4.2	133.8
2SCG4-95	PL12	300	99	4	16	2.8	44.8
2SCG4-96	PL12	300	125	8	32	3.5	113.0
FPL8	PL8	50	50	45	180	0.2	28.3
TOTAL WEIGHT (Kg)						17042.0	
WEIGHT						4260.5	